Eaton 170E3584

Catalog Number: 170E3584

Eaton Bussmann series high speed traction fuse, 80A, 100 kAIC, Other, Fuse, Class gR

General specifications



Eaton Bussmann series high speed

traction fuse

EAN

5996516006382

Product Height

61 mm

Product Weight

942 g

Compliances

IEC

Catalog Number

170E3584

UPC

051712390309

Product Length/Depth

129 mm

Product Width

43 mm

Warranty

Not Applicable



defaultTaxonomyAttributeLabel

Type Fuse Application traction Amperage Rating 80 A Breaking capacity 100 kA Voltage type DC Utilization category gR (general purpose semiconductor protection) Insulated metal gripping lugs (IMGL) No Fuse indicator Other Fuse size 1* Watt losses 13 W Fuse shape Square body, slotted center bolted tags Pre arc (I2T) 1750 Mounting dimension M8 Center-to-center distance of connections 156 mm Current type DC Rated voltage DC 750 V Color None

Interrupt rating

Resources

Catalogs

Traction fuse-links

170E3584~Eaton Bussmann series high speed traction fuse

Bussmann series complete full line catalog no. 1007

100 kAIC

Construction size

Other

Packaging type

Standard

Voltage rating

750 V

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia