

Eaton 170M1360

Catalog Number: 170M1360

Fuse-link, high speed, 20 A, AC 690 V, DIN 000, 21 x 40 x 100 mm, gR, DIN, IEC, single indicator

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1360
	Model Code
	FUSE 20A 690V 000/80 GR UC
UPC	EAN
051712216616	5027590440806
Product Length/Depth	Product Height
105 mm	46 mm
Product Width	Product Weight
300 mm	145.1 g
Warranty	Compliances
Not Applicable	CE Marked
	RoHS Compliant
Certifications	
IEC Rated	
UL Recognized	



defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

20 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

gR (general purpose semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Center-to-center distance of connections

76.7 mm

Current type

AC

Mounting dimension

M8

Class

Class gR

Clearing (I2T)

78 at 660 V

Watt losses

7 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Catalogs

170M1360-FUSE 20A 690V 000/80 GR UC

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M size 000 10A to 315A

UKCA 170M size 000 10A to 315A

Pre arc (I2T)

11.5

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia