

Eaton ESD25

Catalog Number: ESD25

Fuse-link, LV, 25 A, AC 550 V, BS88/F2, 14 x 68 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	ESD25
	UPC
	051712844574
EAN	Product Length/Depth
5027590498630	67 mm
Product Height	Product Width
14 mm	14 mm
Product Weight	Compliances
30.5 g	CE Marked
	RoHS Compliant
Certifications	
IEC 60269-2	
BS88	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

25 A

Fitted with:

Offset bladed tags

Fuse size

BS88/F2

Current type

AC

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

550 V

Class

Class gG/gL

Fuse type

ESD

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

2 W

Connection

Resources

Catalogs

CA134002EN

Compliance information

UKCA ESD

CE ESD

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4101 ESD fuses

Technical service bulletins

Datasheet - ESD25

Blade end

Construction

BS88/F2

Construction size

F2

Fuse shape

Offset bladed tags

Voltage type

AC

Suitable for

63ENS Safeloc fuse holder

SC63 Safeclip fuse holder

Voltage rating

550 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)