

# Eaton NSD16

Catalog Number: NSD16

Fuse-link, LV, 16 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage british standard fuse	NSD16
	<b>UPC</b>
	051712840262
<b>EAN</b>	<b>Product Length/Depth</b>
5027590504799	60 mm
<b>Product Height</b>	<b>Product Width</b>
14 mm	14 mm
<b>Product Weight</b>	<b>Warranty</b>
14.95 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC 60269-2
RoHS Compliant	BS88

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

general industrial applications

### Amperage Rating

16 A

### Fitted with:

Offset bladed tags

### Fuse size

BS88/F1

### Current type

AC

### Breaking capacity

80 kA

### Rated switching capacity

80 kA

### Rated voltage AC

550 V

### Class

Class gG/gL

### Fuse type

NSD

### Utilization category

gL/gG (cable protection/equipment protection)

### Color

None

### Interrupt rating

80 kAIC

### Fuse indicator

None

### Insulated metal gripping lugs (IMGL)

No

### Watt losses

1.8 W

### Connection

## Resources

### Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

### Compliance information

CE NSDx, NSD20Mx, NSD32Mx

UKCA NSDx, NSD20Mx, NSD32Mx

### Multimedia

Eaton Bussmann - Red Spot fuse links

### Technical data sheets

4100 NSD fuses

Blade end

Construction

BS88/F1

Construction size

F1

Fuse shape

Offset bladed tags

Voltage type

AC

Suitable for

32NNS Safeloc fuse holder

SC32 Safeclip fuse holder

Voltage rating

550 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)