

Eaton NSD2

Catalog Number: NSD2

Fuse-link, LV, 2 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	NSD2
	UPC
	051712840279
EAN	Product Length/Depth
5027590504805	60 mm
Product Height	Product Width
14 mm	14 mm
Product Weight	Warranty
16.2 g	Not Applicable
Compliances	Certifications
CE Marked	IEC 60269-2
RoHS Compliant	BS88

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

2 A

Fitted with:

Offset bladed tags

Fuse size

BS88/F1

Current type

AC

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

550 V

Class

Class gG/gL

Fuse type

NSD

Contact material

Offset blade tag, HRC

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

CE NSDx, NSD20Mx, NSD32Mx

UKCA NSDx, NSD20Mx, NSD32Mx

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4100 NSD fuses

0.9 W

Connection

Blade end

Construction

BS88/F1

Construction size

F1

Fuse shape

Offset bladed tags

Voltage type

AC

Suitable for

32NNS Safeloc fuse holder

SC32 Safeclip fuse holder

Quantity

20

Voltage rating

550 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)