

Eaton NSD25

Catalog Number: NSD25

Fuse-link, LV, 25 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	NSD25
	UPC
	051712840316
EAN	Product Length/Depth
5027590504867	58.5 mm
Product Height	Product Width
13.8 mm	13.8 mm
Product Weight	Warranty
16.2 g	Not Applicable
Compliances	
RoHS Compliant	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

general industrial applications

Amperage Rating

25 A

Fitted with:

Offset bladed tags

Fuse size

BS88/F1

Current type

AC

Breaking capacity

80 kA

Rated switching capacity

80 kA

Rated voltage AC

550 V

Class

Class gG/gL

Fuse type

NSD

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

80 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

2 W

Connection

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA NSDx, NSD20Mx, NSD32Mx

CE NSDx, NSD20Mx, NSD32Mx

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4100 NSD fuses

Blade end

Construction

BS88/F1

Construction size

F1

Fuse shape

Offset bladed tags

Voltage type

AC

Suitable for

32NNS Safeloc fuse holder

SC32 Safeclip fuse holder

Voltage rating

550 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia