

# Eaton SSD2

Catalog Number: SSD2

Fuse-link, LV, 2 A, AC 240 V, BS88/E1, 12 x 47 mm, gL/gG, BS



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series low voltage british standard fuse	SSD2
	<b>UPC</b>
	051712841269
<b>EAN</b>	<b>Product Length/Depth</b>
5027590511766	47 mm
<b>Product Height</b>	<b>Product Width</b>
12 mm	12 mm
<b>Product Weight</b>	<b>Warranty</b>
11.6 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	BS88
RoHS Compliant	IEC 60269-2

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

street lighting cut-outs

### Amperage Rating

2 A

### Fitted with:

Offset bladed tags

### Fuse size

BS88/E1

### Current type

AC

### Breaking capacity

33 kA

### Rated switching capacity

33 kA

### Rated voltage AC

240 V

### Class

Class gG/gL

### Fuse type

SSD

### Utilization category

gL/gG (cable protection/equipment protection)

### Color

None

### Interrupt rating

33 kAIC

### Fuse indicator

None

### Insulated metal gripping lugs (IMGL)

No

### Watt losses

0.5 W

### Connection

## Resources

### Catalogs

CA134002EN

SSD2–Eaton Bussmann series low voltage British standard fuse

Bussmann series complete full line catalog no. 1007

### Compliance information

CE Industrial offset blade tag and cylindrical fuse-links

UKCA Industrial offset blade tag and cylindrical fuse-links

### Multimedia

Eaton Bussmann - Red Spot fuse links

### Technical data sheets

4105 SSD fuses

Blade end

Construction

BS88/E1

Construction size

E1

Fuse shape

Offset bladed tags

Voltage type

AC

Suitable for

SC20 Safeclip fuse holder

Voltage rating

240 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)