

Eaton SSD4

Catalog Number: SSD4

Fuse-link, LV, 4 A, AC 240 V, BS88/E1, 12 x 47 mm, gL/gG, BS



General specifications

Product Name	Catalog Number
Eaton Bussmann series low voltage british standard fuse	SSD4
	UPC
	051712841290
EAN	Product Length/Depth
5027590511810	47 mm
Product Height	Product Width
12 mm	12 mm
Product Weight	Warranty
11.6 g	Not Applicable
Compliances	Certifications
CE Marked	BS88
RoHS Compliant	IEC 60269-2

defaultTaxonomyAttributeLabel

Type

Fuse

Application

street lighting cut-outs

Amperage Rating

4 A

Fitted with:

Offset bladed tags

Fuse size

BS88/E1

Current type

AC

Breaking capacity

33 kA

Rated switching capacity

33 kA

Rated voltage AC

240 V

Class

Class gG/gL

Fuse type

SSD

Utilization category

gL/gG (cable protection/equipment protection)

Color

None

Interrupt rating

33 kAIC

Fuse indicator

None

Insulated metal gripping lugs (IMGL)

No

Watt losses

1 W

Connection

Resources

Catalogs

CA134002EN

Bussmann series complete full line catalog no. 1007

SSD4~Eaton Bussmann series low voltage British standard fuse

Compliance information

UKCA Industrial offset blade tag and cylindrical fuse-links

CE Industrial offset blade tag and cylindrical fuse-links

Multimedia

Eaton Bussmann - Red Spot fuse links

Technical data sheets

4105 SSD fuses

Blade end

Construction

BS88/E1

Construction size

E1

Fuse shape

Offset bladed tags

Voltage type

AC

Suitable for

SC20 Safeclip fuse holder

Voltage rating

240 V

Fuse system (according to IEC 60269)

Fuse system E



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)