



## EE-SX670A

Photo micro sensor, slot type, standard shape, L-ON/D-ON selectable, NPN, connector

# Specifications

<b>Shape</b>	Straight
<b>Sensing method</b>	Through-beam with slot
<b>Sensing distance</b>	5 mm
<b>Setting method</b>	Fixed
<b>Connection method</b>	System connector
<b>Output type</b>	NPN
<b>Operation mode</b>	Dark-ON, Light-ON
<b>Response time</b>	0.17 ms
<b>Material housing</b>	PBT
<b>Thread size</b>	Other
<b>Product Width (unpacked)</b>	25.4 mm
<b>Product Height (unpacked)</b>	22.2 mm
<b>Product Depth (unpacked)</b>	6.95 mm
<b>Type of light</b>	Infrared light
<b>Supply voltage DC</b>	5-24 V

# Accessories



EE-1001

Accessory Connector for Photomicrosensors, 4-pin , solder terminals



EE-1001-1

Connector for Photomicrosensors, 4-pin , solder terminals, bridge between L and +



EE-1006 1M

Accessory Photomicro sensor connector with cable 1 m



EE-1006 2M

Accessory Photomicro sensor connector with cable 2 m



EE-1006 3M

Accessory Photomicro sensor connector with cable 3m



EE-1010 2M

Accessory Photomicro sensor EE-SPX\_03, cable connector, PVC, 2m



EE-1010-R 2M

Accessory photomicro sensor EE-SPX\_03, cable connector, robotic PVC, 2 m

# Downloads

CAD Library



**EE-SX47/67 Slot-type  
Photomicrosensor (Non-  
modulated)**

Datasheet

EN PDF 2.06 MB

