



P2RF-05-PU

Socket, DIN rail/surface mounting, 15.5 mm, 5-pin, Push-in terminals

Specifications

Applicable product family	G2R-1-S, H3RN
Mounting method	DIN rail/screw
Product Depth (unpacked)	52.1 mm
Product Height (unpacked)	90 mm
Product Width (unpacked)	15.5 mm
Terminal	Push-in Plus
Color	Black
Hold down clip included	✓
Release Lever included	✓

Fits to



G2R-1-S 120VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 120 VAC



G2R-1-S 12VDC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 12 VDC



G2R-1-S 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 230 VAC



G2R-1-S 240VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical indicator, 240 VAC

**G2R-1-S 24VAC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 24 VAC

**G2R-1-S 24VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech indicator, label facility, 24 VDC

**G2R-1-SD 24VDC (S)**

Relay, plug-in, SPDT, 10 A, mech. indicator, diode, 24 VDC

**G2R-1-SN 110VAC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility

**G2R-1-SN 110VDC (S)**

Relay, plug-in, SPDT, 10 A, mechanical & LED indicator, 110 VDC

**G2R-1-SN 120VAC (S)**

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 120 VAC

**G2R-1-SN 12VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility

**G2R-1-SN 230VAC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility

**G2R-1-SN 240VAC (S)**

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, 240 VAC

**G2R-1-SN 24VAC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility

**G2R-1-SN 24VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility

**G2R-1-SN 48VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, label facility, 48 VDC

**G2R-1-SN-AP3 230VAC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating

**G2R-1-SN-AP3 24VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, gold-plated contacts, LED indicator

**G2R-1-SND 12VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, 12 VDC

**G2R-1-SND 24VDC (S)**

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility



G2R-1-SND 48VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility



G2R-1-SND-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, label facility, Au-plating



G2R-1-SNDI 12VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC



G2R-1-SNDI 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-1-SNDI-AP3 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A gold plate contacts, mech & LED indicators, coil suppressor, lockable test button, label facility



G2R-1-SNI 110VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility, 110 AC



G2R-1-SNI 120VAC (S)

Relay, plug-in, SPDT, 10 A, mech. & LED indicator, test button, 120 VAC



G2R-1-SNI 12VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility



G2R-1-SNI 12VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility



G2R-1-SNI 230VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility



G2R-1-SNI 24VAC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility



G2R-1-SNI 24VDC (S)

Relay, plug-in, 5-pin, SPDT, 10 A, mech & LED indicators, lockable test button, label facility



G2R-1-SNI 48VAC (S)

Relay, plug-in, SPDT, 10 A, mechanical & LED indicator, lockable testbutton, 48 VAC



G2R-1-SNI-AP3 230VAC (S)

Relay, plug-in, SPDT (gold plated), 10 A, mech. & LED indicator, test button, 230 VAC

Accessories



MG-CPM-04 41390N

White modular sheet with 48 marker of size mm: 5x10, Polycarbonate, Halogen Free, Silicon Free, UL94 V0, -40° to 130°C, Minimum Order Quantity is 1 box (In one box: 35 sheets, total markers 1680)

PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

PFP-100N2

DIN-rail mounting track, 35x16mm, 1m length

PFP-50N

Din rail track, 500 mm



PFP-M

End plate

PFP-S

Spacer



PYDN-15.5-080R

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Red color



PYDN-15.5-080S

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Blue color



PYDN-15.5-080Y

Accessory for PYF-PU, 15.5mm pitch, 8 Poles, Yellow color



PYDN-7.75-020R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Red color



PYDN-7.75-020S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Blue color



PYDN-7.75-020Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 2 Poles, Yellow color




PYDN-7.75-030R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Red color




PYDN-7.75-030S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Blue color



PYDN-7.75-030Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 3 Poles, Yellow color



PYDN-7.75-040R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Red color



PYDN-7.75-040S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Blue color



PYDN-7.75-040Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 4 Poles, Yellow color



PYDN-7.75-200R

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Red color



PYDN-7.75-200S

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Blue color



PYDN-7.75-200Y

Accessory for PYF-PU/P2RF-PU, 7.75mm pitch, 20 Poles, Yellow color



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width



XW5Z-EP6

End bracket for terminal blocks, 6 mm width

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



PYF-__-PU/PTF-__- PU/P2RF-__-PU Sockets with Push-In Plus technology Datasheet

EN PDF 2.53 MB