



P2RF-08-S

Socket, DIN rail/surface mounting, 8-pin, screwless terminals

Specifications

Applicable product family	G2R-2-S
Mounting method	DIN rail/screw
Product Depth (unpacked)	32.6 mm
Product Height (unpacked)	92 mm
Product Width (unpacked)	18 mm
Terminal	Screwless clamp
Color	Beige
Hold down clip included	✓
Release Lever included	✓
Applicable ferrules	Forked terminals, Round terminals

Fits to



G2R-2-S 12VDC (S)

Relay, plug-in, 8-pin, DPDT, 10 A, mech indicator, label facility, 12 VDC



G2R-2-S 220VAC (S)

Relay, plug-in, 5 A, mechanical indicator, 220 VAC



G2R-2-S 230VAC (S)

Relay, plug-in, DPST, 10 A, mechanical indicator, 230 VAC



G2R-2-S 240VAC (S)

Relay, plug-in, DPDT, 5 A, mechanical indicator, 240 VAC

**G2R-2-S 24VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 24 VAC

**G2R-2-S 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, label facility, 24 VDC

**G2R-2-SD 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech indicators, coil suppressor, label facility

**G2R-2-SN 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VAC

**G2R-2-SN 110VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VDC

**G2R-2-SN 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

**G2R-2-SN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VAC

**G2R-2-SN 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VDC

**G2R-2-SN 230VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 230 VAC

**G2R-2-SN 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 24 VAC

**G2R-2-SN 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 24 VDC

**G2R-2-SN 48VAC**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VAC

**G2R-2-SN 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VDC

**G2R-2-SN-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SND 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 12 VDC

**G2R-2-SND 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility

**G2R-2-SND 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 48 VDC

**G2R-2-SND-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, mech & LED indicators, coil suppressor, label facility

**G2R-2-SNDI 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility, 12 VDC

**G2R-2-SNDI 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility

**G2R-2-SNDI 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility

**G2R-2-SNDI-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label test button, Au-plating

**G2R-2-SNI 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 120 VAC

**G2R-2-SNI 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 12VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility, 12 VDC

**G2R-2-SNI 230VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 240 VAC

**G2R-2-SNI 24VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 48VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI-AP3 230VAC (S)**

Relay, plug-in, DPDT (gold plated), 5 A, mech. & LED indicator, test button, 230 VAC



P2CM-S

Clip for use with P2RF-S



P2RM-SB

Socket bridge (for use with P2RF_S)

PFP-S

Spacer



XW5Z-EP12

Separator Plate for terminal blocks, 12 mm width

CAD Library



EAC Mark removal Discontinuation Notice

EN PDF 221 KB



G2R-_-S (S) General- purpose Relay Datasheet

EN PDF 3.9 MB



G3R-I/O Solid State Relays Datasheet

EN PDF 2.82 MB



H3RN Solid-state Timer Datasheet

EN PDF 2.13 MB



H3RN-_-B Solid-state timer Datasheet

EN PDF 1.59 MB



K7L-AT50(D) Liquid Leakage Sensor Amplifiers Datasheet

EN PDF 1.87 MB



K7L-series Liquid Leakage Sensor Amplifiers Datasheet

EN PDF 7.11 MB



P2RF-05-ESS Relay Sockets Datasheet

EN PDF 496 KB



P2RF-08-ESS Relay Sockets Datasheet

EN PDF 480 KB



PYC-TR Relay Sockets Datasheet

EN PDF 198 KB



PYF-_-PU/PTF-_- PU/P2RF-_-PU Sockets with Push-In Plus technology Datasheet

EN PDF 2.53 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 24 April, 2024. Click here for [terms of use](#).