



## S8VK-X12024A-EIP

Book type power supply, 120 W, 24 VDC, 5 A, DIN rail mounting, Push-in terminal, Coated, display, Ethernet IP / Modbus TCP compatibility

# Specifications

Type	Book type
Mounting method	DIN rail
Phase	Single
Power output	120 W
Efficiency	92 %
Output voltage	24 V
Rated output current	5 A
Power boost ratio	120 %
Temperature range	-40-70 °C
Terminal	Push-in
Communication port(s)	EtherNet/IP, MODBUS/TCP
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Product Width (unpacked)	55 mm
Product Height (unpacked)	94.7 mm
Product Depth (unpacked)	92.3 mm

PFP-100N

DIN-rail mounting track, 35 x 7.3 mm, 1 m length

## Related products



### Electronic Circuit Breaker

S8V-CP - Electronic Circuit Breaker



### S8V-NF

Noise Filter S8V-NF

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### Perfect Power Supply Solutions Brochure

EN PDF 807 KB



### Predictive Maintenance Solutions Vol.1 Flyer

EN PDF 4.01 MB



### Predictive Maintenance Solutions Vol.2 Flyer

EN PDF 5.93 MB



### Predictive Maintenance Solutions Vol.3 Flyer

EN PDF 3.35 MB



### Predictive Maintenance Solutions Vol.4 Flyer

EN PDF 7.19 MB



### Predictive Maintenance Solutions Vol.5 Flyer

EN PDF 3.96 MB



### S8VK Series Switch Mode Power Supplies Brochure

EN PDF 2.03 MB



### S8VK X Power Supply Monitoring Tool Software

EN ZIP 110 MB



### S8VK-X EtherNet/IP EDS file

EN ZIP 28.2 KB




### S8VK-X Switch Mode Power Supply Communications Manual

EN PDF 1.23 MB



### S8VK-X Switch Mode Power Supply Datasheet

EN PDF 6.54 MB



### S8VK-X and NX PLC - Ethernet Communication Software

EN ZIP 2.01 MB