

PABA WH/23 - Insert label



1013779

<https://www.phoenixcontact.com/in/products/1013779>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Commercial data

Item number	1013779
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG2
Product key	BG2213
Catalog page	Page 129 (PC-2007)
GTIN	4017918013967
Weight per piece (including packing)	8.1 g
Weight per piece (excluding packing)	5.69 g
Customs tariff number	39269097
Country of origin	CN

Technical data

Notes

General	Can be labeled with CMS
---------	-------------------------

Product properties

Product type	Conductor marking
--------------	-------------------


Data management status

Article revision	01
------------------	----

Marking

Number of individual labels	20
Number of individual labels per row	1

Dimensions

Dimensional drawing	
Width	23 mm
Text field width	23.00 mm
Text field height	4.00 mm
Length	4 mm

Material specifications

Color	white (RAL 9010)
Material	ABS
Flammability rating according to UL 94	V0

Cable/line

External cable diameter	1.5 mm ... 35 mm
-------------------------	------------------

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
---------------	----------------------------------

PABA WH/23 - Insert label



1013779

<https://www.phoenixcontact.com/in/products/1013779>

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 80 °C (105 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-15 °C ... 65 °C
---------------------------------	------------------

PABA WH/23 - Insert label



1013779

<https://www.phoenixcontact.com/in/products/1013779>

Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	slide-on
---------------	----------

PABA WH/23 - Insert label


1013779

<https://www.phoenixcontact.com/in/products/1013779>



Drawings

Dimensional drawing



PABA WH/23 - Insert label



1013779

<https://www.phoenixcontact.com/in/products/1013779>

Classifications

ECLASS

ECLASS-11.0	27281102
ECLASS-12.0	27281102
ECLASS-13.0	27281102

ETIM

ETIM 9.0	EC001530
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

PABA WH/23 - Insert label



1013779

<https://www.phoenixcontact.com/in/products/1013779>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>




Accessories

PLOTMARK - Marking plotter

0804499

<https://www.phoenixcontact.com/in/products/0804499>

Marking plotter for the entire portfolio of UC marking materials and materials in sheet and strip format.




CMS-P1-PLOTTER - Marking plotter

5144615

<https://www.phoenixcontact.com/in/products/5144615>

Marking plotter, weight: 8 kg, length: 0.66 m, width: 440 mm, height: 125 mm, color: silver



PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PAB-KTL 23 - Cable marker carrier

1013957

<https://www.phoenixcontact.com/in/products/1013957>



Cable marker carrier, transparent, unlabeled, horizontal, mounting type: Assembly with cable ties, cable diameter: > 10 mm, lettering field size: 23 x 4 mm

PATG 0/23 - Conductor marker carrier

0828046

<https://www.phoenixcontact.com/in/products/0828046>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 0.6 ... 1.2 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PATG 1/23 - Conductor marker carrier

1013847

<https://www.phoenixcontact.com/in/products/1013847>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 1.5 ... 2.5 mm, lettering field size: 23 x 4 mm

PATG 2/23 - Conductor marker carrier

1013850

<https://www.phoenixcontact.com/in/products/1013850>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>

PATG 3/23 - Conductor marker carrier

1013863

<https://www.phoenixcontact.com/in/products/1013863>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 23 x 4 mm

PATG 4/23 - Conductor marker carrier

0808011

<https://www.phoenixcontact.com/in/products/0808011>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 6 ... 10 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PATG 5/23 - Conductor marker carrier

0808024

<https://www.phoenixcontact.com/in/products/0808024>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 10 ... 14 mm, lettering field size: 23 x 4 mm

PATG 6/23 - Conductor marker carrier

0808037

<https://www.phoenixcontact.com/in/products/0808037>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 14 ... 22 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PATG 7/23 - Conductor marker carrier

0808040

<https://www.phoenixcontact.com/in/products/0808040>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 22 ... 30 mm, lettering field size: 23 x 4 mm

PATG 8/23 - Conductor marker carrier

0808053

<https://www.phoenixcontact.com/in/products/0808053>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 30 ... 35 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PATG HF 1/23 - Conductor marker carrier

1014048

<https://www.phoenixcontact.com/in/products/1014048>



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 1.3 ... 2.8 mm, lettering field size: 23 x 4 mm

PATG HF 2/23 - Conductor marker carrier

1014054

<https://www.phoenixcontact.com/in/products/1014054>



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PATG HF 3/23 - Conductor marker carrier

1014060

<https://www.phoenixcontact.com/in/products/1014060>



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 23 x 4 mm

PATG HF 4/23 - Conductor marker carrier

1014066

<https://www.phoenixcontact.com/in/products/1014066>



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 5 ... 10 mm, lettering field size: 23 x 4 mm

PABA WH/23 - Insert label

1013779

<https://www.phoenixcontact.com/in/products/1013779>



PATO 1/23 - Conductor marker carrier

1013892

<https://www.phoenixcontact.com/in/products/1013892>



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 2 ... 3.5 mm, lettering field size: 4 x 23 mm

PATO 2/23 - Conductor marker carrier

1013902

<https://www.phoenixcontact.com/in/products/1013902>



Conductor marker carrier, transparent, unlabeled, mounting type: clip on, cable diameter range: 2.8 ... 4.4 mm, lettering field size: 4 x 23 mm

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in