

FLK 50/EZ-DR/ 150/SO235 - Cable



2319346

<https://www.phoenixcontact.com/in/products/2319346>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled round cable, with two 50-pos. socket strips (1:1 connection), for transmitting 50 signals, cable length: 1.5 m

Commercial data

Item number	2319346
Packing unit	1 pc
Minimum order quantity	50 pc
Product key	CK2AZZ
GTIN	4046356342834
Weight per piece (including packing)	258.1 g
Weight per piece (excluding packing)	258.1 g
Country of origin	DE

FLK 50/EZ-DR/ 150/SO235 - Cable



2319346

<https://www.phoenixcontact.com/in/products/2319346>

Technical data

Product properties

Product type	System cable
--------------	--------------

Cable/line

Cable length	1.5 m
--------------	-------

50X0.14 [PVC]

UL AWM Style	2464/1061
Number of positions	50
Shielded	no
Cable type	50X0.14 [PVC]
Conductor type	Round cable set
Conductor structure signal line	7x 0.16 mm
AWG signal line	26
Conductor cross section	50x 0.14 mm ²
Wire diameter incl. insulation	1 mm ±0.03 mm
External cable diameter	10.30 mm ±0.4 mm
Outer sheath, material	Semi-rigid PVC
External sheath, color	gray
Conductor material	Tin-plated Cu litz wires
Cable resistance	≤ 145 Ω/km (20 °C)
Insulation resistance	≥ 20 MΩ*km (20 °C)
Smallest bending radius, fixed installation	86 mm
Smallest bending radius, movable installation	161 mm
Max. bending cycles	5000 (at a radius of ≥ 15x outside diameter)
Halogen-free	no
Flame resistance	IEC 60332-1-2 (raw cable) VDE 0842, Part 332-1-2 (raw cable) IEC 60332-3-22 (raw cable) UL VW-1 CSA FT-1
Resistance to oil	can withstand occasional splashes (raw cable)

Connection data

Field level

Connection method	IDC/FLK socket strip
Number of connections	1
Number of positions	50
Pitch	2.54 mm

Controller level

Connection method	IDC/FLK socket strip
-------------------	----------------------

FLK 50/EZ-DR/ 150/SO235 - Cable



2319346

<https://www.phoenixcontact.com/in/products/2319346>

Number of connections	1
Number of positions	50
Pitch	2.54 mm

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

FLK 50/EZ-DR/ 150/SO235 - Cable

2319346

<https://www.phoenixcontact.com/in/products/2319346>



Classifications

ECLASS

ECLASS-11.0	27242220
-------------	----------

FLK 50/EZ-DR/ 150/SO235 - Cable



2319346

<https://www.phoenixcontact.com/in/products/2319346>

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in