

2744814

https://www.phoenixcontact.com/in/products/2744814

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



CAT5-SF/UTP cable (J-02YS(ST)C HP 2 x 2 x 24 AWG), heavy-duty installation cable, 2 x 2 x 0. 22 mm^2 , solid conductor, shielded, outer sheath: 7.8 mm diameter, inner sheath: 5.75 mm \pm 0.15 mm diameter

Commercial Data

Item number	2744814
Packing unit	1 m
Minimum order quantity	1 m
Note	Made to Order (non-returnable)
Sales Key	BF1
Product Key	BF1CJI
Catalog Page	Page 390 (C-8-2015)
GTIN	4017918600518
Weight per Piece (including packing)	66.72 g
Weight per Piece (excluding packing)	45 g
Customs tariff number	85444993
Country of origin	DE



https://www.phoenixcontact.com/in/products/2744814



Technical Data

Product properties

Product type	Data cable by the meter
Number of positions	4
Sensor type	Ethernet
Shielded	yes

Electrical properties

Nominal voltage U _N	48 V AC
Transmission medium	Copper

Interfaces

Signal type/category	Ethernet CAT5 (IEC 11801), 100 Mbps

Cable/line

Cable length	Free input (0.25 1000.0 m)
External sheath, color	blue

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C 80 °C (cable, fixed installation)
	-5 °C 60 °C (Cable, flexible installation)
Ambient temperature (storage/transport)	-40 °C 80 °C



2744814

https://www.phoenixcontact.com/in/products/2744814

Approvals



EAC-RoHS

Approval ID: RU D-DE.HB35.B.00395



2744814

https://www.phoenixcontact.com/in/products/2744814

Classifications

ECLASS

	ECLASS-11.0	27061801
	ECLASS-12.0	27061801
	ECLASS-13.0	27061801
ETIM		
	ETIM 8.0	EC003249
UNSPSC		
	UNSPSC 21.0	26121600



https://www.phoenixcontact.com/in/products/2744814



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/in/products/2744814



Accessories

FL PLUG RJ45 GR/2 - RJ45 connector

2744856

https://www.phoenixcontact.com/in/products/2744856



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Plastic, connection method: Crimp connection, cable outlet: straight, color: green, Ethernet

FL PLUG RJ45 GN/2 - RJ45 connector

2744571

https://www.phoenixcontact.com/in/products/2744571



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Plastic, connection method: Crimp connection, cable outlet: straight, color: green, Ethernet



https://www.phoenixcontact.com/in/products/2744814



FL CRIMPTOOL - Assembly tool

2744869

https://www.phoenixcontact.com/in/products/2744869

Crimping pliers, for assembling the RJ45 plugs FL PLUG RJ45..., for assembly on site



FL-PP-RJ45-SCC - Patch panels

2901642

https://www.phoenixcontact.com/in/products/2901642



Patch panel, one RJ45 jack to 8 spring-force connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers



https://www.phoenixcontact.com/in/products/2744814



FL-PP-RJ45-SC - Patch panels

2901643

https://www.phoenixcontact.com/in/products/2901643



Patch panel, one RJ45 jack to 8 screw connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers

FL-PP-RJ45-LSA - Patch panels

2901645

https://www.phoenixcontact.com/in/products/2901645



Patch panel, one RJ45 jack to 8 LSA connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via bridges



https://www.phoenixcontact.com/in/products/2744814



FL-PP-RJ45/RJ45 - Patch panels

2901646

https://www.phoenixcontact.com/in/products/2901646



Patch panel, two RJ45 jacks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers

FL ISOLATOR 100-RJ/RJ - Network isolator

2313931

https://www.phoenixcontact.com/in/products/2313931



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Possible to connect two RJ45 plugs.



https://www.phoenixcontact.com/in/products/2744814



FL ISOLATOR 1000-RJ/RJ - Network isolator

2313915

https://www.phoenixcontact.com/in/products/2313915



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 1 Gbps. Possible to connect two RJ45 plugs.

FL RJ45 PROTECT CAP - Dust protection

2832991

https://www.phoenixcontact.com/in/products/2832991



Dust protection caps for RJ45 socket



https://www.phoenixcontact.com/in/products/2744814



FL CAT5 HEAVY CONF/ - Network cable

2744827

https://www.phoenixcontact.com/in/products/2744827



CAT5-SF/UTP cable (J-02YS(ST)C HP 2 x 2 x 24 AWG), heavy-duty installation cable, 2 x 2 x 0.22 $\,\text{mm}^2$, solid conductor, shielded, outer sheath: 7.8 mm diameter, inner sheath: 5.75 mm \pm 0.15 mm diameter, preassembled on both sides with RJ45 plug, crossover or line

FL CAT5 FLEX - Installation cable

2744830

https://www.phoenixcontact.com/in/products/2744830



By the meter, Installation cable, Ethernet CAT5 (100 Mbps), shielded, PUR halogen-free, water blue RAL 5021, 4-wire (2x2xAWG26/7; SF/UTP), color single wire: white/orange-orange, white/green-green, cable length: Free entry (1. 0 ... 1000.0 m)



https://www.phoenixcontact.com/in/products/2744814



FL CAT5 FLEX CONF/ - Network cable

2744843

https://www.phoenixcontact.com/in/products/2744843



CAT5-SF/UTP cable (J-Ll02YS(ST)C H 2 x 2 x 26 AWG), light-duty, flexible installation cable 2 x 2 x 0.14 mm 2 , stranded, shielded, outer sheath: 5.75 mm \pm 0.15 mm diameter, preassembled on both sides with RJ45 plug, crossover or line assignment

FL CAT5 TERMINAL BOX - Patch panels

2744610

https://www.phoenixcontact.com/in/products/2744610



Patch panel, one RJ45 jack to 4 screw connection terminal blocks (assignment 1, 2, 3, 6), CAT5e, 10/100 Mbps, DIN rail adapter, IP20, shield contacting on DIN rail

Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in