


PLC-TR-1T-MUL-300M - Timer relay



2910140

<https://www.phoenixcontact.com/in/products/2910140>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Multi-function timer relay with 4 functions in an ultra-narrow design, adjustable time range (0.1 s - 300 min), 1 changeover contact, screw connection

Commercial Data

Item number	2910140
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	CK4
Product Key	CK4521
Catalog Page	Page 262 (C-5-2019)
GTIN	4055626430492
Weight per Piece (including packing)	59.6 g
Weight per Piece (excluding packing)	50.9 g
Customs tariff number	85364900
Country of origin	DE

Technical Data

Product properties

Product type	Timer relay
Operating mode	100% operating factor
Mechanical service life	approx. 2×10^7 cycles

Insulation characteristics

Insulation	Basic insulation
------------	------------------

Insulation characteristics

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	2

Electrical properties

Service life electrical	approx. 2×10^5 cycles at ohmic load, 1000 VA
Nominal power consumption	0.45 W (at 24 V DC)
Rated insulation voltage	300 V AC
Rated surge voltage	6 kV

Input data

Nominal power consumption	0.45 W (at 24 V DC)
Input voltage range	24 V DC (19.2 V DC ... 30 V DC)
Recovery time	50 ms
Setting range time	0.1 s ... 300 min. (4 time end ranges)
Setting accuracy	≤ 2.5 % (of scale end value)
Repeat accuracy	≤ 0.5 % (of scale end value)

Control

Connection name	Non-floating, terminals A1-B1
Control pulse length	≥ 50 ms

Output data

Switching

Contact type	1 floating changeover contact
Maximum switching voltage	250 V AC
Interrupting rating (ohmic load) max.	1500 VA (6 A / 250 V AC)
Output fuse	6.3 A (fast-blow)

Connection data

Connection method	Screw connection
Stripping length	8 mm
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 2.5 mm ²

PLC-TR-1T-MUL-300M - Timer relay



2910140

<https://www.phoenixcontact.com/in/products/2910140>

Conductor cross section AWG	30 ... 12
Tightening torque	0.6 Nm ... 0.8 Nm ()
	5 lbf-in. ... 7 lbf-in.

Signaling

Status display	Green LED (POWER)
	Yellow LED (relay active)

Dimensions

Width	6.2 mm
Height	80 mm
Depth	86 mm

Material specifications

Flammability rating according to UL 94	V0
Housing insulation material	Polyamide PA, self-extinguishing

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-25 °C ... 80 °C
Altitude	≤ 2000 m
Permissible humidity (operation)	15 % ... 85 %

Approvals

CE

Identification	CE-compliant
----------------	--------------

UL, USA/Canada

Identification	UL/C-UL Listed UL 508
----------------	-----------------------

EMC data

Low Voltage Directive	Conformance with Low Voltage Directive
Noise immunity	EN 61000-6-2
Electromagnetic compatibility	Conformance with EMC directive
Noise emission	EN 61000-6-3

Standards and regulations

Standards/regulations	IEC 61812-1
	IEC 60947-5-1

Mounting

Mounting type	DIN rail mounting
Assembly instructions	on standard DIN rail NS 35 in accordance with EN 60715

PLC-TR-1T-MUL-300M - Timer relay



2910140

<https://www.phoenixcontact.com/in/products/2910140>

Mounting position

any

PLC-TR-1T-MUL-300M - Timer relay



2910140

<https://www.phoenixcontact.com/in/products/2910140>

Approvals



DNV GL

Approval ID: TAA00002RX



UL Listed

Approval ID: FILE E 172140



cUL Listed

Approval ID: FILE E 172140

PLC-TR-1T-MUL-300M - Timer relay



2910140

<https://www.phoenixcontact.com/in/products/2910140>

Classifications

ECLASS

ECLASS-11.0	27371605
ECLASS-12.0	27371605
ECLASS-13.0	27371605

ETIM

ETIM 8.0	EC001439
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

PLC-TR-1T-MUL-300M - Timer relay



2910140

<https://www.phoenixcontact.com/in/products/2910140>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in