



## AZM 170-02ZRI-B6L 24VAC/DC

- 1 Cable entry M 20 x 1.5
- IDC method of termination
- Manual release
- Double-insulated
- Individual coding
- Coding level "High" according to ISO 14119
- 90 mm x 84 mm x 30 mm
- Compact design
- Interlock with protection against incorrect locking.
- Long life
- High holding force
- left-hand model
- For very small actuating radii in line with or at 90° to the plane of the actuator

## Data

### Ordering data

Product type description	AZM 170-02ZRI-B6L 24VAC/DC
Article number (order number)	101140810
EAN (European Article Number)	4030661119984
eCl@ss number, version 12.0	27-27-26-03
eCl@ss number, version 11.0	27-27-26-03
eCl@ss number, version 9.0	27-27-26-03
ETIM number, version 7.0	EC002593
ETIM number, version 6.0	EC002593

### Approvals - Standards

Certificates	BG cULus CCC
--------------	--------------------

## General data

Standards	BG-GS-ET-19 EN ISO 13849-1 EN ISO 14119 EN IEC 60947-5-1
Coding	Individual coding
Coding level according to EN ISO 14119	High
Working principle	electromechanical
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the actuator	Stainless steel
Gross weight	305 g

## General data - Features

Power to unlock	Yes
Manual release	Yes
Number of actuating directions	2
Number of safety contacts	2

## Safety classification

Standards	EN ISO 13849-1
Performance Level, up to	d
Category	3
Mission time	20 Year(s)

## Safety classification - Safety outputs

B <sub>10D</sub> Normally-closed contact (NC)	2,000,000 Operations
---	----------------------

### Safety classification - Fault exclusion

Mission time	20 Year(s)
--------------	------------

### Mechanical data

Actuating radius, minimum	50 mm
Mechanical life, minimum	1,000,000 Operations
Holding force $F_{Zh}$ in accordance with EN ISO 14119	1,000 N
Holding force $F_{max}$ , maximum	1,300 N
Latching force	30 N
Positive break travel	11 mm
Positive break force per NC contact, minimum	8.5 N
Positive break force, minimum	17 N
Actuating speed, maximum	2 m/s
Mounting	Screws
Type of the fixing screws	2x M5

### Mechanical data - Connection technique

Cable entry	M 16 x 1.5
Termination	IDC method of termination
Cable section, minimum	0.75 mm <sup>2</sup>
Cable section, maximum	1 mm <sup>2</sup>
Allowed type of cable	flexible

### Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	90 mm
Height of sensor	84 mm

## Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +60 °C
Storage and transport temperature, minimum	+25 °C
Storage and transport temperature, maximum	+85 °C
Protection class	II

## Ambient conditions - Insulation values

Rated insulation voltage $U_i$	250 VAC
Rated impulse withstand voltage $U_{imp}$	4 kV
Overvoltage category	III
Degree of pollution	3

## Electrical data

Thermal test current	6 A
Rated control voltage	24 VAC/DC
Required rated short-circuit current	1,000 A
Electrical power consumption, maximum	10 W
Switching element	Opener (NC)
Note (Switching element)	Change-over contact with double break, type Zb or 2 NC or 3 NC or 4 NC contacts, with galvanically separated contact bridges
Switching principle	slow action, positive break NC contact
Switching frequency	1,000 /h
Material of the contacts, electrical	Silver

## Electrical data - Magnet control

Magnet switch-on time	100 %
-----------------------	-------

Test pulse duration, maximum	5 ms
Test pulse interval, minimum	50 ms

## Electrical data - Safety contacts

Voltage, Utilisation category AC-15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	2.5 A

## Other data

Note (applications)	sliding safety guard removable guard hinged safety guard
---------------------	--

## Scope of delivery

Scope of delivery	Not available as spare part Slot sealing plugs The actuator is included in the scope of delivery
-------------------	--

## Note

Note (General)	This type termination (IDC) method enables simple connection of flexible conductors without the need for the use of conductor ferrules The actuator is not available separately.
Note (Manual release)	bottom For manual release using M5 triangular key, available as accessory

## Ordering code

Product type description:  
AZM 170(1)-(2)Z(3)I(4)-(5)-(6)-(7) (8)

<b>without</b>	Cut clamps
<b>SK</b>	Screw connection
(2)	
<b>11</b>	1 NO contacts/1 NC contact
<b>02</b>	2 NC contact
(3)	
<b>without</b>	Latching force 5 N
<b>R</b>	Latching force 30 N
<b>I</b>	Individual coding
(4)	
<b>without</b>	Power to unlock
<b>A</b>	Power to lock
(5)	
<b>without</b>	cable gland
<b>ST</b>	M12 x 1 connector
(6)	
<b>B1</b>	with actuator B1
<b>B5</b>	with actuator B5
<b>B6L</b>	with actuator B6L
<b>B6R</b>	with actuator B6R
(7)	
<b>without</b>	Manual release
<b>2197</b>	Manual release from side (Standard in case of conector and power to unlock versions)
<b>1637</b>	Gold-plated contacts
(8)	
<b>24VAC/DC</b>	Us 24 VAC/DC
<b>110VAC</b>	Us 110 VAC

**230VAC**

Us 230 VAC

(1)

---

<b>11/11</b>	1 NO contact, 1 NC contact / 1 NO contact 1, NC contact
<b>11/02</b>	1 NO contact, 1 NC contact / 2 NC contacts
<b>12/00</b>	1 NO contact, 2 NC contacts / -
<b>12/11</b>	1 NO contact, 2 NC contact / 1 NO contact 1, NC contact
<b>12/02</b>	1 NO contact, 2 NC contact / 2 NC contacts
<b>02/01</b>	2 NC contacts / 1 NC contact
<b>02/10</b>	2 NC contacts, - / 1 NO contact

(2)

---

<b>without</b>	Latching force 5 N
<b>R</b>	Latching force 30 N

(3)

---

<b>without</b>	Power to unlock
<b>A</b>	Power to lock

(4)

---

<b>B1</b>	with actuator B1
<b>B5</b>	with actuator B5
<b>B6L</b>	with actuator B6L
<b>B6R</b>	with actuator B6R

(5)

---

<b>1637</b>	Gold-plated contacts
-------------	----------------------

(6)

---

<b>2197</b>	Manual release for Power to unlock
-------------	------------------------------------

**Pictures**

## Product picture (catalogue individual photo)




ID: kazm1fi3

| 595.8 kB | .jpg | 262.114 x 331.258 mm - 743 x 939 px - 72 dpi

| 49.6 kB | .png | 74.083 x 93.486 mm - 210 x 265 px - 72 dpi

| 54.5 kB | .jpg | 97.719 x 123.472 mm - 277 x 350 px - 72 dpi

## Dimensional drawing basic component




ID: kazm1gi3

| 106.0 kB | .cdr |

| 6.2 kB | .png | 74.083 x 83.961 mm - 210 x 238 px - 72 dpi

| 195.9 kB | .jpg | 352.778 x 400.403 mm - 1000 x 1135 px - 72 dpi

## Dimensional drawing actuator




ID: 1azm1b35

| 139.7 kB | .jpg | 352.778 x 317.853 mm - 1000 x 901 px - 72 dpi

| 17.8 kB | .png | 74.083 x 66.675 mm - 210 x 189 px - 72 dpi

## Switch travel diagram



ID: kazm1s01


| 19.5 kB | .cdr |

| 1.8 kB | .png | 74.083 x 26.458 mm - 210 x 75 px - 72 dpi

| 49.4 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355 px - 72 dpi

## Diagram






ID: kazm1k11

| 55.1 kB | .ai | 297 x 210.002 mm - 841 x 595 px - 72 dpi

| 47.2 kB | .jpg | 352.778 x 112.183 mm - 1000 x 318 px - 72 dpi

| 2.5 kB | .png | 74.083 x 23.636 mm - 210 x 67 px - 72 dpi

## Operating principle



ID: kazm1a70

| 213.5 kB | .jpg | 352.778 x 656.519 mm - 1000 x 1861 px - 72 dpi

| 6.5 kB | .png | 74.083 x 137.583 mm - 210 x 390 px - 72 dpi

## Assembly example



ID: kazm1m06

| 98.4 kB | .cdr |

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/12/2023, 7:02 am