



## AZM40B-ST-1P2P-PH

- Compact, flat design
- 119,5 mm x 40 mm x 20 mm
- High holding force 2000
- Latching force 40 N
- RFID-technology for needs-based protection against tampering
- Individually coded version with coding level "High" according to ISO 14119
- Only one version for hinged and sliding doors
- Actuator can approach interlock continuously within a 180 degree angle.
- Symmetrical mounting, can be bolted on either side

## Data

### Ordering data

|                               |                   |
|-------------------------------|-------------------|
| Product type description      | AZM40B-ST-1P2P-PH |
| Article number (order number) | 103037330         |
| EAN (European Article Number) | 4030661543727     |
| eCl@ss number, version 12.0   | 27-27-26-03       |
| eCl@ss number, version 11.0   | 27-27-26-03       |
| eCl@ss number, version 9.0    | 27-27-26-03       |
| ETIM number, version 7.0      | EC002593          |
| ETIM number, version 6.0      | EC002593          |

### Approvals - Standards

|              |                                     |
|--------------|-------------------------------------|
| Certificates | TÜV<br>cULus<br>FCC<br>IC<br>ANATEL |
|--------------|-------------------------------------|

## General data

|  |   |
|--|---|
| Standards  | EN ISO 13849-1<br>EN ISO 14119<br>EN IEC 60947-5-3<br>EN IEC 61508                          |
| Coding   | Universal coding  |
| Coding level according to EN ISO 14119                                 | Low   |
| Working principle  | RFID  |
| Frequency band RFID  | 125 kHz   |
| Transmitter output RFID, maximum                                       | -6 dB/m   |
| Housing material   | Light alloy die cast and plastic (glass-fibre reinforced thermoplastic, self-extinguishing) |
| Reaction time, maximum   | 100 ms  |
| Duration of risk, maximum  | 200 ms  |
| Reaction time, switching off safety outputs via safety inputs, maximum | 1.5 ms  |
| Gross weight   | 304 g   |

## General data - Features

|                                     |     |
|-------------------------------------|-----|
| Actuator monitored                  | Yes |
| Latching                            | Yes |
| Manual release                      | Yes |
| Short circuit detection             | Yes |
| Cross-circuit detection             | Yes |
| Series-wiring                       | Yes |
| Safety functions                    | Yes |
| Integral system diagnostics, status | Yes |
| Number of safety contacts           | 2   |

## Safety classification

|           |                                |
|-----------|--------------------------------|
| Standards | EN ISO 13849-1<br>EN IEC 61508 |
|-----------|--------------------------------|

## Safety classification - Interlocking function

|  |                          |
|--|--------------------------|
| Performance Level, up to                                   | e                        |
| Category   | 4                        |
| PFH value  | $1.10 \times 10^{-9}$ /h |
| PFD value  | $8.90 \times 10^{-5}$    |
| Safety Integrity Level (SIL), suitable for applications in | 3                        |
| Mission time   | 20 Year(s)               |

## Mechanical data

|  |                      |
|--|----------------------|
| Interlocking principle                                 | bistable             |
| Mechanical life, locking cycles                        | 1,000,000 Operations |
| Mechanical life, actuator cycles                       | 200,000 Operations   |
| Holding force $F_{Zh}$ in accordance with EN ISO 14119 | 2,000 N              |
| Holding force $F_{max}$ , maximum                      | 2,600 N              |
| Latching force   | 40 N                 |
| Note (Latch force)                                     | +/- 25%              |
| Actuating speed, maximum                               | 0.5 m/s              |
| Mounting   | mounting holes plain |
| Type of the fixing screws                              | 2x M5                |
| Tightening torque of the fixing screws, minimum        | 4 Nm                 |

## Mechanical data - Switching distances according EN IEC 60947-5-3

|   |      |
|---|------|
| Assured switching distance "ON" $S_{ao}$  | 1 mm |
| Assured switching distance "OFF" $S_{ar}$ | 8 mm |

## Mechanical data - Connection technique

|                                 |      |
|---------------------------------|------|
| Length of sensor chain, maximum | 30 m |
|---------------------------------|------|

|                                   |  |
|-----------------------------------|--|
| Note (length of the sensor chain) | Cable length and cross-section change the voltage drop depending on the output current                     |
| Note (series-wiring)              | Unlimited number of devices, observe external line fusing, max. 31 devices in case of serial diagnostic SD |
| Termination                       | Connector M12, 8-pole, A-coded   |

### Mechanical data - Dimensions

|                  |          |
|------------------|----------|
| Length of sensor | 119.5 mm |
| Width of sensor  | 40 mm    |
| Height of sensor | 20 mm    |

### Ambient conditions

|  |                              |
|--|------------------------------|
| Degree of protection                                       | IP67<br>IP66                 |
| Ambient temperature  | +0 ... +55 °C                |
| Storage and transport temperature, minimum                 | -40 °C                       |
| Storage and transport temperature, maximum                 | +85 °C                       |
| Relative humidity, maximum                                 | 93 %                         |
| Note (Relative humidity)                                   | non-condensing<br>non-icing  |
| Resistance to vibrations                                   | 10 ... 55 Hz, amplitude 1 mm |
| Resistance to shock  | 30 g / 11 ms                 |
| Protection class   | III                          |
| Permissible installation altitude above sea level, maximum | 2,000 m                      |

### Ambient conditions - Insulation values

|   |        |
|---|--------|
| Rated insulation voltage $U_i$            | 32 VDC |
| Rated impulse withstand voltage $U_{imp}$ | 0.8 kV |
| Overtoltage category                      | III    |
| Degree of pollution                       | 3      |

## Electrical data

|  |   |
|--|---|
| Operating voltage                                    | 24 VDC -15 % / +10 % (stabilised PELV power supply) |
| No-load supply current $I_0$ , typical               | 100 mA  |
| Current consumption magnet at switching moment, peak | 600 mA / 100 ms                                     |
| Rated operating voltage                              | 24 VDC  |
| Operating current                                    | 1,200 mA  |
| Required rated short-circuit current                 | 100 A   |
| External wire and device fuse rating                 | 2 A gG  |
| Time to readiness, maximum                           | 4,000 ms  |
| Switching frequency, maximum                         | 0.25 Hz   |
| Utilisation category DC-12                           | 24 VDC / 0.05 A                                     |

## Electrical data - Magnet control

|                                     |  |
|-------------------------------------|--|
| Designation, Magnet control         | IN   |
| Switching thresholds                | -3 V ... 5 V (Low)<br>15 V ... 30 V (High) |
| Magnet switch-on time               | 100 %                                      |
| Test pulse duration, maximum        | 5 ms                                       |
| Test pulse interval, minimum        | 40 ms                                      |
| Classification ZVEI CB24I, Sink     | C0   |
| Classification ZVEI CB24I, Source   | C1<br>C2<br>C3                             |
| Current consumption at 24V, minimum | 10 mA                                      |
| Current consumption at 24V, maximum | 15 mA                                      |

## Electrical data - Safety digital inputs

|                             |  |
|-----------------------------|--|
| Designation, Safety inputs  | X1 and X2                                  |
| Switching thresholds        | -3 V ... 5 V (Low)<br>15 V ... 30 V (High) |
| Current consumption at 24 V | 5 mA                                       |

|                                   |                |
|-----------------------------------|----------------|
| Test pulse duration, maximum      | 1 ms           |
| Test pulse interval, minimum      | 100 ms         |
| Classification ZVEI CB24I, Sink   | C1             |
| Classification ZVEI CB24I, Source | C1<br>C2<br>C3 |

### Electrical data - Safety digital outputs

|  |                             |
|--|-----------------------------|
| Designation, Safety outputs              | Y1 and Y2                   |
| Rated operating current (safety outputs) | 250 mA                      |
| Design of control elements               | short-circuit proof, p-type |
| Voltage drop $U_d$ , maximum             | 2 V                         |
| Leakage current $I_r$ , maximum          | 0.5 mA                      |
| Voltage, Utilisation category DC-12      | 24 VDC                      |
| Current, Utilisation category DC-12      | 0.25 A                      |
| Voltage, Utilisation category DC-13      | 24 VDC                      |
| Current, Utilisation category DC-13      | 0.25 A                      |
| Test pulse interval, typical             | 1000 ms                     |
| Test pulse duration, maximum             | 0.5 ms                      |
| Classification ZVEI CB24I, Source        | C2                          |
| Classification ZVEI CB24I, Sink          | C1<br>C2                    |

### Electrical data - Diagnostic outputs

|                                     |                             |
|-------------------------------------|-----------------------------|
| Designation, Diagnostic outputs     | OUT                         |
| Design of control elements          | short-circuit proof, p-type |
| Voltage drop $U_d$ , maximum        | 2 V                         |
| Voltage, Utilisation category DC-12 | 24 VDC                      |
| Current, Utilisation category DC-12 | 0.05 A                      |
| Voltage, Utilisation category DC-13 | 24 VDC                      |
| Current, Utilisation category DC-13 | 0.05 A                      |

## Status indication

Note (LED switching conditions display)

Operating condition: LED green  
Error / functional defect: LED red  
Supply voltage UB: LED green

## Pin assignment

|       |                       |
|-------|-----------------------|
| PIN 1 | A1 Supply voltage UB  |
| PIN 2 | X1 Safety input 1     |
| PIN 3 | A2 GND                |
| PIN 4 | Y1 Safety output 1    |
| PIN 5 | OUT Diagnostic output |
| PIN 6 | X2 Safety input 2     |
| PIN 7 | Y2 Safety output 2    |
| PIN 8 | IN Solenoid control   |

## Accessory

Recommendation (actuator) AZM40-B1-PH

## Ordering code

Product type description:  
AZM40(1)-(2)-ST-1P2P-(3)

(1)

---

**Z** Guard locking monitored

**B** Actuator monitored

(2)

---

**without** Standard coding

**I1** Individual coding

**I2** Individual coding, re-teaching enabled

(3)

---

without

Counterbores for countersunk screws (standard)

PH

Flat enclosure for protruding screws

## Pictures

### Product picture (catalogue individual photo)




ID: kaz40f24

| 1.1 MB | .jpg | 352.778 x 866.422 mm - 1000 x 2456 px - 72 dpi

| 100.3 kB | .png | 74.083 x 181.681 mm - 210 x 515 px - 72 dpi

| 28.5 kB | .jpg | 50.447 x 123.472 mm - 143 x 350 px - 72 dpi


### Dimensional drawing basic component



ID: kaz40g01

| 126.0 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000 px - 72 dpi


### Dimensional drawing basic component



ID: kaz40g03

| 51.4 kB | .jpg | 352.778 x 160.514 mm - 1000 x 455 px - 72 dpi

### Wiring example



ID: kaz40I01

| 5.1 kB | .png | 74.083 x 49.389 mm - 210 x 140 px - 72 dpi

| 108.5 kB | .jpg | 352.778 x 234.244 mm - 1000 x 664 px - 72 dpi



The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 08/12/2023, 12:13 pm