



SCG01.103

- Head positioned to the front
- Metal enclosure
- 50 mm x 120 mm x 43 mm
- Long life

Data

Ordering data

Product type description	SCG01.103
Article number (order number)	101020914
EAN (European Article Number)	4030661610221
eCl@ss number, version 12.0	27-27-26-02
eCl@ss number, version 11.0	27-27-26-02
eCl@ss number, version 9.0	27-27-26-02
ETIM number, version 7.0	EC002592
ETIM number, version 6.0	EC002592

Approvals - Standards

Certificates	cULus
--------------	-------

General data

Standards	BG-GS-ET-15 EN ISO 14119 EN IEC 60947-5-1
Housing material	Aluminium
Housing coating material	painted

Gross weight	325 g
--------------	-------

General data - Features

Number of auxiliary contacts	1
------------------------------	---

Number of safety contacts	1
---------------------------	---

Safety classification

Standards	EN ISO 13849-1
-----------	----------------

Mission time	20 Year(s)
--------------	------------

Safety classification - Safety outputs

B _{10D} Normally-closed contact (NC)	2,000,000 Operations
---	----------------------

B _{10D} Normally open contact (NO)	1,000,000 Operations
---	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
--------------------------	----------------------

Positive break travel	11 mm
-----------------------	-------

Positive break force, minimum	5 N
-------------------------------	-----

Note (Positive break force)	per NC
-----------------------------	--------

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
-------------	---------------------------

Cable section, minimum	0.5 mm ²
------------------------	---------------------

Cable section, maximum	2.5 mm ²
------------------------	---------------------

Note (Cable section)	All indications including the conductor ferrules.
----------------------	---

Mechanical data - Dimensions

Length of sensor	43 mm
------------------	-------

Width of sensor	50 mm
Height of sensor	120 mm

Ambient conditions

Degree of protection	IP67
Ambient temperature	-25 ... +70 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	400 V
Rated impulse withstand voltage U_{imp}	2.5 kV

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
Switching element	NO contact, NC contact
Switching principle	Slow action
Material of the contacts, electrical	Silver

Scope of delivery

Scope of delivery	Actuator must be ordered separately.
-------------------	--------------------------------------

Ordering code

Product type description:
SCG(1)/(2)

(1)

01 Head positioned to the front

02	Head positioned to the left
03	Head positioned to the right
04	Head positioned to the rear
(2)	
103	1 NC contact / 1 NO contact slow action switching contact
220	2 NC contacts slow action switching contact
92	1 NC contact / 1 NO contact snap switching element

Pictures

Product picture (catalogue individual photo)




ID: kscg-f01

| 89.7 kB | .png | 74.083 x 144.286 mm - 210 x 409 px - 72 dpi

| 1.0 MB | .jpg | 320.675 x 625.122 mm - 909 x 1772 px - 72 dpi

| 45.8 kB | .jpg | 63.5 x 123.472 mm - 180 x 350 px - 72 dpi

Dimensional drawing basic component




ID: kshg-g02

| 31.0 kB | .cdr |

| 4.0 kB | .png | 74.083 x 48.331 mm - 210 x 137 px - 72 dpi

| 108.9 kB | .jpg | 352.778 x 229.306 mm - 1000 x 650 px - 72 dpi

Switch travel diagram




ID: kshg-s02

| 19.6 kB | .cdr |

| 1.5 kB | .png | 74.083 x 17.992 mm - 210 x 51 px - 72 dpi

| 33.4 kB | .jpg | 352.778 x 85.019 mm - 1000 x 241 px - 72 dpi

Diagram



ID: ktzg-k01

| 53.1 kB | .jpg | 352.778 x 128.058 mm - 1000 x 363 px - 72 dpi

| 2.7 kB | .png | 74.083 x 26.811 mm - 210 x 76 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 08/12/2023, 8:19 am