



Figure similar

Spare part SIMATIC S7-200, Digital I/O EM 223, only for S7-22X CPU, 8 DI 24 V DC, Sink/Source, 8 DO 24 V DC; 0.75 A/channel source

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	80 mA
Power loss	
Power loss, typ.	3 W
Digital inputs	
Number of digital inputs	8
Input voltage	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	0 to 5 V
• for signal "1"	15 V DC to 30 V DC
Input current	
• for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	4.5 ms
Digital outputs	
Number of digital outputs	8
Short-circuit protection	No
Limitation of inductive shutdown voltage to	L+ (-48 V)
Output voltage	
• for signal "0", max.	0.1 V
• for signal "1", min.	20 V
Output current	
• for signal "1" rated value	750 mA
Total current of the outputs (per group)	
all mounting positions	
— Current per conductor/group, max.	3 A
Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	0.75 A; each output
— on lamp load, max.	5 W
— with resistive load, max.	0.75 A; each output
Cable length	

- shielded, max. 500 m
- unshielded, max. 150 m

Encoder

Connectable encoders

- 2-wire sensor Yes
- permissible quiescent current (2-wire sensor), max. 1 mA

Potential separation

Potential separation digital inputs

- Potential separation digital inputs Yes; Optocoupler
- between the channels, in groups of 4

Potential separation digital outputs

- Potential separation digital outputs Yes; Optocoupler
- between the channels, in groups of 4

Isolation

Isolation tested with 500 V AC

connection method

Plug-in I/O terminals Yes

Dimensions

Width 71.2 mm
 Height 80 mm
 Depth 62 mm

Weights

Weight, approx. 200 g

last modified: 5/22/2024 