



Figure similar

SIMATIC S7-200 SMART, Analog input SM AI04, 4 AI, 0...10V, 0...5V, +/-5 V, +/-2.5 V, or 0/4-20 mA 11 bit + sign (12 bit ADC)

| General information | |
|---|--|
| Product type designation | SM AI04, AI 4x12 bit |
| CiR - Configuration in RUN | |
| Reparameterization possible in RUN | No |
| Supply voltage | |
| Type of supply voltage | DC |
| Rated value (DC) | 24 V; -15 / +20 % |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Input current | |
| Current consumption, typ. | 40 mA |
| from backplane bus 5 V DC, typ. | 80 mA |
| Power loss | |
| Power loss, typ. | 1.5 W |
| Analog inputs | |
| Number of analog inputs | 4 |
| Input ranges | |
| <ul style="list-style-type: none"> • Voltage • Current • Thermocouple • Resistance thermometer • Resistance | <ul style="list-style-type: none"> Yes; ±10V, ±5V, ±2.5V Yes; 0 to 20 mA No No No |
| Input ranges (rated values), voltages | |
| <ul style="list-style-type: none"> • -10 V to +10 V <ul style="list-style-type: none"> — Input resistance (-10 V to +10 V) • -2.5 V to +2.5 V <ul style="list-style-type: none"> — Input resistance (-2.5 V to +2.5 V) • -5 V to +5 V <ul style="list-style-type: none"> — Input resistance (-5 V to +5 V) | <ul style="list-style-type: none"> Yes 9 MΩ Yes 9 MΩ Yes 9 MΩ |
| Input ranges (rated values), currents | |
| <ul style="list-style-type: none"> • 0 to 20 mA <ul style="list-style-type: none"> — Input resistance (0 to 20 mA) | <ul style="list-style-type: none"> Yes 250 Ω |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Interference voltage suppression for interference frequency f1 in Hz | <ul style="list-style-type: none"> 12 bit; voltage mode: 11 bit + sign bit, current mode: 11 bit 10 / 50 / 60 / 400 Hz |
| Smoothing of measured values | |
| <ul style="list-style-type: none"> • parameterizable | <ul style="list-style-type: none"> Yes; In 4 stages: 1x, 4x, 16x, 32x cycle time |

- Step: None
- Step: low
- Step: Medium
- Step: High

Yes; 1x
 Yes; 4x
 Yes; 16x
 Yes; 32x

Interrupts/diagnostics/status information

| | |
|--|--|
| Diagnostics function | Yes |
| Diagnoses | |
| <ul style="list-style-type: none"> • Monitoring the supply voltage • Wire-break • Short-circuit | <p>Yes No No</p> |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> • for status of the inputs | Yes |

Degree and class of protection

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Standards, approvals, certificates

| | |
|---------|-----|
| CE mark | Yes |
|---------|-----|

Dimensions

| | |
|--------|--------|
| Width | 45 mm |
| Height | 100 mm |
| Depth | 81 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 147 g |
|-----------------|-------|

last modified: 3/12/2024 