



Figure similar

MLFB-Ordering data

6SL3210-5DE13-5UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
Input		Cooling	
Number of phases	3 AC	natural convection	
Line voltage	380 ... 480 V -15 % +10 %	Installation altitude	
Line frequency	45 ... 66 Hz	1000 m	
Output		Cooling air requirement	
Rated power	1.00 kW	0.005 m³/s ( 0.177 ft³/s )	
Rated current (IN)	3.00 A	Ambient temperature	
Max. output current	9.00 A	Operation	
Electronic power supply		0 ... 45 °C (32 ... 113 °F)	
Power supply	24 V ±10 %	Storage	
General tech. specifications		-40 ... 70 °C (-40 ... 158 °F)	
Power loss	47.00 W	Transport	
Connections		-40 ... 70 °C (-40 ... 158 °F)	
Motor end		Relative humidity	
Conductor cross-section	1.5 mm²	Max. operation	
Mechanical data		90 %	
Degree of protection	IP20 / UL open type	Standards	
Frame size	FSA	Compliance with standards	
Net weight	1.85 kg ( 4.08 lb )	CE	
Width	80.0 mm ( 3.15 in )		
Height	180.0 mm ( 7.09 in )		
Depth	200.0 mm ( 7.87 in )		