Data Sheet | Item Number: 706-100/1300-400

Connection cable; 20-pole; Pluggable connector per DIN 41651; open-ended;

Length: 4 m; Conductor cross-section: 0.14 mm²; UR components







| Color coding | | 20-pole connector | |
|----------------|-------------|----------------------|---|
| acc. to DIN VD | E 47100 | Contact number | 1 |
| white | | 1 | 1 |
| brown | 상 첫 | 2 | 1 |
| green | | 3 | 1 |
| yellow | | 4 | 1 |
| grey | | 5 | 1 |
| pink | | 6 | 1 |
| blue | 8 9 | 7. | 1 |
| red | | 8 | 1 |
| black | S | 9 | 1 |
| violet. | | 10 | i |
| grey/pink | New Control | 11 | 1 |
| red/blue | | 12 | 1 |
| white/green | | 13 | 1 |
| brownigreen | | 14 | 1 |
| white/yellow | | 15 | 1 |
| yellow/brown | | 16 | 1 |
| white/gray | | 17- | 1 |
| grey/brown | | 18 | 1 |
| white-pink | | 19 | 1 |
| pink/brown | | 20 | 1 |

Similar to illustration

| Notes | |
|-------|---|
| Note | When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A. |

| Electrical data | |
|-------------------------|--------------|
| Operating voltage | ≤ AC/DC 35 V |
| Current per wire (max.) | 1 A |

| Connection data | | | |
|------------------------------|--------------------|--|--|
| Cable type | LiYY | Connection 1 | |
| Color code per DIN VDE 47100 | Connector | Pluggable connector per DIN 41651; fe- male connector | |
| | Pole number 1 | 20 | |
| | Connection type 1 | System | |
| | Wire cross-section | 0.14 mm ² | |

| Connection 2 | |
|-------------------|------------|
| Connector 2 | open-ended |
| Connection type 2 | open-ended |

| Physical data | | |
|---------------|-----|--|
| Cable length | 4 m | |

Data Sheet | Item Number: 706-100/1300-400

https://www.wago.com/706-100/1300-400



Material data

Fire load 0 MJ Weight 205 g

Environmental requirements

Ambient temperature (operation) -20 ... +50 °C

Commercial data **Product Group** 30 (WAGO France) eCl@ss 10.0 27-06-03-11 eCl@ss 9.0 27-06-03-11 ETIM 8.0 EC001855 ETIM 7.0 EC001855 PU (SPU) 1 pcs Packaging type Box FR Country of origin **GTIN** 4050821674528

85444290900

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Customs tariff number

Environmental Product Compliance 706-100/1300-400



1 Compatible Products

1.1 Optional Accessories

1.1.1 Interface module

1.1.1.1 Interface module



Item No.: 704-2004

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 1-wire connection; in mounting carrier



Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier

4

Item No.: 704-2044

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 2-wire connection; in mounting carrier

Item No.: 704-2054

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel digital input or output; 3-wire connection; in mounting carrier



Item No.: 704-5004

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Double-deck PCB terminal blocks; in mounting carrier; 2,50 mm²



Item No.: 704-5014 Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay

gable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Doubledeck PCB terminal blocks; without relay; in mounting carrier; 2,50 mm²



Item No.: 704-5034

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; PCB terminal blocks; with output fuse; in mounting carrier; 2.50 mm²



Item No.: 704-5024
Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; in mounting carrier; 2.50 mm²

Data Sheet | Item Number: 706-100/1300-400

https://www.wago.com/706-100/1300-400



1.1.1.1 Interface module



Item No.: 704-5044

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 changeover contact; Triple-deck PCB terminal blocks; with manual operation; in mounting carrier; 2,50 mm²



Item No.: 704-5054

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



<u>Item No.: 704-5074</u>

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 1 make contact; with disconnect terminal block and fuse; in mounting carrier; 2,50 mm²



Item No.: 704-5064

2,50 mm²

Interface module for system wiring; Pluggable connector per DIN 41651; Male connector; 20-pole; 16-channel relay output; 2 changeover contacts; Double-deck PCB terminal blocks; in mounting carrier;

Item No.: 289-614

Interface module; Pluggable connector per DIN 41651; 20-pole; Triple-deck PCB terminal blocks; in mounting carrier; 2,50

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at:: www.wago.com

Version 21.04.2024 Page 3/3