




Data Sheet | Item Number: 756-5401/060-150

Sensor/Actuator cable; M12A socket; straight; M12A plug; straight; 5-pole; Length: 15 m

<https://www.wago.com/756-5401/060-150>



Similar to illustration



Short description:

- PUR, halogen-free
- Suitable for drag chains
- High resistance to microbes, hydrolysis, oil, chemicals and UV radiation
- High chemical resistance
- Cable used: UL listed

Technical data

General information

Operating voltage	250 VAC/DC
Operating current	4 A
Rated surge voltage	1.5 kV
Insulation resistance	$\geq 1.6 \times 10^{10} \Omega/\text{km}$
Contact resistance	10 m Ω
Conductor resistance	< 57 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

Drag chain compatible

Bending diameter (min.)	52 mm
Bending radius	10 x cable diameter (min.)
Bending cycles	2 million
Acceleration (min.)	10 m/s ²
Travel speed (max.)	4 m/s
Travel path (horizontal) max.	15 m
Torsional capacity	180 °/m

Cable		Connector	
Cable length	15 m	Connection type	M12 Socket - M12 plug
Type code	Li9YC11Y-HF 5x0.34 mm ²	Pole number	5
Overall shield	Tinned copper braid, optical coverage approx. 80 %	Cable connection direction to mating direction	0 °
Conductor configuration	Bare copper wire (7 x 0.25 mm)	Cable connection direction to mating direction (2)	0 °
Conductor insulation	Halogen-free PE	Connector interface coding (cable/adapter) 1 1	A-coded
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing	Connector interface coding (cable/adapter) 2 1	A-coded
Sheathed cable color	black	Housing material	Polyurethane (PUR)
Sheathed cable diameter	6.3 ... 6.7 mm	Contact material	CuSn
		Tightening torque	1 Nm

Commercial data	
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	HU
GTIN	4050821844129
Customs tariff number	85444290900

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 2238	E519602

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 756-5401/060-150	↓

Documentation

System Description

IP67 Cables and Plug-
gable Connectors

pdf
157.80 KB

