


# Data Sheet | Item Number: 756-5510/030-020

Sensor/Actuator cable; M8 socket; angled; M12A plug; angled; 3-pole; Length: 2 m



<https://www.wago.com/756-5510/030-020>



Similar to illustration



Pin 1 ... 4: 0.25 mm<sup>2</sup>



Dimensions in mm

## Short description:

- PUR, halogen-free
- Suitable for drag chains
- Good resistance to microbes, hydrolysis, oil, chemicals and UV radiation.
- Good chemical resistance.
- Cable used: UL listed

## Technical data

### General information

Operating voltage	AC/DC 60 V
Operating current	4 A
Rated surge voltage	1.5 kV
Insulation resistance	>10 <sup>9</sup> Ω
Contact resistance	10 mΩ
Conductor resistance	≤ 60 Ω/km
Pollution degree	3 per VDE 0110
Protection type	IP67
Ambient (operating) temperature (static)	-50 ... +90 °C
Ambient (operating) temperature (dynamic)	-25 ... +90 °C

### Drag chain compatible

Bending radius	10 x cable diameter (min.)
Bending cycles	2 million
Acceleration (min.)	5 m/s <sup>2</sup>
Travel speed (max.)	3.33 m/s
Travel path (horizontal) max.	5 m
Travel path (vertical) max.	2 m
Torsional capacity	180 °/m



Cable	
Cable length	2 m
Type code	LiF9YH-11YH or LiF9YC11YFHF
Conductor configuration	Bare copper wire, fine-stranded (42 x 0.1 mm)
Conductor insulation	PP9Y (halogen-free)
Sheath material	Polyurethane (PUR), halogen-free per DIN VDE 0472 Part 815, flame resistant per IEC 332-2, self-extinguishing
Sheathed cable color	black
Sheathed cable diameter	3.9 ... 4.3 mm

Connector	
Connection type	M8 socket - M12 plug
Pole number	3
Cable connection direction to mating direction	90 °
Cable connection direction to mating direction (2)	90 °
Connector interface coding (cable/adapter) 2 1	A-coded
Housing material	Polyurethane (PUR)
Contact material	CuSn
Tightening torque	0.6 ... 1 Nm

Commercial data	
eCl@ss 10.0	27-06-03-11
eCl@ss 9.0	27-06-03-11
ETIM 8.0	EC001855
ETIM 7.0	EC001855
PU (SPU)	10 (1) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918975926
Customs tariff number	85444290900

Environmental Product Compliance	
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c)

### Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 756-5510/030-020	<a href="#">↓</a>

### Documentation

System Description		
IP67 Cables and Plug-gable Connectors	pdf 157.80 KB	<a href="#">↓</a>

Bid Text			
756-5510/030-020	19.02.2019	xml 3.21 KB	<a href="#">↓</a>
756-5510/030-020	20.09.2017	doc 25.50 KB	<a href="#">↓</a>

CAD/CAE-Data

CAE data

WSCAD Universe  
756-5510/030-020

