

**H1,0/14S GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



- Polypropylene conical cable entry funnel
  - Heat-resistant up to 105°C
- For conductors from 0.5 – 10.0 mm<sup>2</sup> (AWG 20-7)  
Material: E-Cu, tin galvanised  
Dimensional tolerance acc. to DIN 46228 sect. 4

**General ordering data**

|            |   |
|------------|---|
| Version    | Wire-end ferrule, Standard, 10 mm, 8 mm, yellow |
| Order No.  | <a href="#">9025970000</a>                      |
| Type       | H1,0/14S GE                                     |
| GTIN (EAN) | 4008 190063733                                  |
| Qty.       | 500 pc(s).                                      |
| Packaging  | loose   |

Creation date August 1, 2024 10:21:42 AM CEST

Catalogue status 13.07.2024 / We reserve the right to make technical changes.

**H1,0/14S GE****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight 0.104 g

**Technical data**

|                        |  |         |          |
|------------------------|--|---------|----------|
| Description of article | Wire end ferrule with plastic collar, special size, yellow | Version | Standard |
|------------------------|--|---------|----------|

**Wire-end ferrules**

|                             |                   |   |             |
|-----------------------------|-------------------|---|-------------|
| Collar diameter (D2)        | 3.5 mm            | Colour code                             | Weidmueller |
| Conductor cross-section     | 1 mm <sup>2</sup> | Contact surface diameter (D1)           | 1.4 mm      |
| Contact surface length (L2) | 8 mm              | L1 in mm                                | 14 mm       |
| Metal sleeve thickness (S1) | 0.15 mm           | Plastic collar thickness (S2)           | 0.25 mm     |
| Stripping length            | 10 mm             | Wire connection cross section AWG, max. | AWG 17      |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000005    | ETIM 7.0    | EC000005    |
| ETIM 8.0    | EC000005    | ETIM 9.0    | EC000005    |
| ECLASS 9.0  | 27-40-02-01 | ECLASS 9.1  | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |
| ECLASS 12.0 | 27-40-02-01 | ECLASS 13.0 | 27-40-02-01 |

**Environmental Product Compliance**

|                        |                             |
|------------------------|-----------------------------|
| REACH SVHC             | /                           |
| RoHS Compliance Status | Compliant without exemption |

**Approvals**

Approvals



|                         |            |
|-------------------------|------------|
| ROHS                    | Conform    |
| UL File Number Search   | UL Website |
| Certificate no. (cULus) | E499744    |

**Downloads**

|                    |  |
|--------------------|--|
| Engineering Data   | <a href="#">CAD data – STEP</a>  |
| User Documentation | <a href="#">Technical information - EN</a><br><a href="#">Technical information - DE</a> |
| Catalogues         | <a href="#">Catalogues in PDF-format</a>   |
| Brochures          |  |

**Data sheet**

**H1,0/14S GE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**

