

# Eaton 100LET

Catalog Number: 100LET

Eaton Bussmann series high speed British standard fuse, 100A, 280 VAC/150 VDC (UL), Class aR, 200 kA RMS Sym., Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed british standard fuse	100LET
	<b>EAN</b>
	5027590427791
<b>UPC</b>	<b>Product Length/Depth</b>
051712830294	55 mm
<b>Product Height</b>	<b>Product Width</b>
18 mm	18 mm
<b>Product Weight</b>	<b>Compliances</b>
30.3 g	CE Marked
	RoHS Compliant
<b>Certifications</b>	
IEC Rated	
UL Recognized	
Designed and tested to BS88 part 4	
IEC 60269-4	

## Electrical data

### Amperage Rating

100 A

### Voltage rating

280 V

### Rated voltage AC

280 V

### Rated voltage DC

150 V

### Interrupt rating

200 kA RMS Sym, 50 kA DC at 150 Vdc

### Class

Class aR

### Pre arc (I2T)

600

### Clearing (I2T)

7500

### Watt losses

10 W

## Product specifications

### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

### Fuse indicator

None

## Compatible Trip indicator/Microswitch

### Suitable for

TI500 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

## Resources

### Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

### Catalogues

[IEC high speed fuse links](#)

### Certification reports

[DA-DC-00004685](#)

[DA-DC-00004682](#)

### Technical data sheets

[720004 LCT, LET, LMMT, LMT](#)