

Eaton 15ET

Catalog Number: 15ET

Eaton Bussmann series high speed British standard fuse, Single barrel, 15A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed british standard fuse	15ET
	Packing Unit
	Case Pack
	Pack
EAN	Quantity
5027590353892	480
5027590033176	10
Gross Weight	Length
20.456 kg	385 mm
0.404 kg	82 mm
Width	Height
280 mm	175 mm
91 mm	39 mm
Volume	ERP Name
18865 cm ³	SAP-UNITY
291.018 cm ³	SAP-UNITY
Product Length/Depth	Product Height
76 mm	20 mm
Product Width	Product Weight
20 mm	40.4 g

Compliances

RoHS Compliant

Electrical data

Amperage Rating

15 A

Voltage rating

690 V (IEC), 700 V (UL)

Rated voltage AC

690 V

Rated voltage DC

500 V

Interrupt rating

200 kA RMS Sym, 50 kA at 500 Vdc

Class

Class aR

Pre arc (I2T)

11

Clearing (I2T)

60 at 415 V, 95 at 660 V

Watt losses

4.6 W

Product specifications

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Fuse indicator

None

Compatible Trip indicator/Microswitch

Suitable for

EC-600 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

Resources

Brochures

[eaton-bussmann-series-bs88-high-speed-fuses-product-aid-pa135003en-us.pdf](#)

Catalogs

[IEC high speed fuse links](#)

Certification reports

[DA-DC-00004682](#)

[DA-DC-00004685](#)