

Eaton 170M1371

Catalog Number: 170M1371

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 250 A, 200 kAIC, Top fuse status indicator, Fuse, Blade end X blade end, Class aR, DIN 43 620



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1371
	Packing Unit
	Pack
	Case Pack
EAN	Quantity
5027590337892	10
5027590345064	70
Gross Weight	Length
1.306 kg	105 mm
9.142 kg	385 mm
Width	Height
300 mm	46 mm
280 mm	175 mm
Volume	ERP Name
14490 cm ³	SAP-UNITY
18865 cm ³	SAP-UNITY
Product Length/Depth	Product Height
105 mm	46 mm
Product Width	Product Weight
300 mm	130.6 g
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

250 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

000

Rated voltage AC

690 V

Center-to-center distance of connections

76.7 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I2T)

51500 at 660 V

Watt losses

42 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Compliance information

UKCA 170M size 000 10A to 315A

CE 170M size 000 10A to 315A

Pre arc (I2T)

7750

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

000

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)