

Eaton 170M1572D

Catalog Number: 170M1572D

Fuse-link, high speed, 315 A, AC 690 V, 200 kA, DIN 00, aR, DIN, IEC, type T indicator, square body with knife blade contacts

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M1572D
	UPC
	051712334938
EAN	Product Length/Depth
5027590441421	79 mm
Product Height	Product Width
69 mm	30 mm
Product Weight	Warranty
204 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated



defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

315 A

Breaking capacity

200 kA

Fuse indicator

Combination fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Current type

AC

Class

Class aR

Clearing (I2T)

84500 at 660 V

Watt losses

45 W

Fuse shape

Square body, knife blade contacts

Pre arc (I2T)

12000

Color

None

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Compliance information

UKCA NH-style, high-speed dual indicator fuselinks

CE NH-style, high-speed dual indicator fuselinks

Installation videos

Eaton's Switch disconnectors and Bussmann series fuses for MOEM

Applications (brightcove.net)

Technical data sheets

720101 DIN 43620 690V Dual ind

Interrupt rating

200 kAIC

Fitted with:

Dual indicator

Connection

Din 43-620 blade end x Din 43-620 blade end

Construction size

00

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43620

Bladed

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)