



Fuse-link, high speed, 315 A, AC 690 V, size 000, 24 x 36 x 96 mm, aR, IEC, UL

Part no. **FUSE 315A 750V DC IEC aR 000FU/70**
170M1761

Similar to illustration

General specifications		
Product name		Eaton Bussmann series high speed square body fuse
Part no.		FUSE 315A 750V DC IEC aR 000FU/70
EAN		5027590441575
Product Length/Depth		140 millimetre
Product height		42 millimetre
Product width		101 millimetre
Product weight		156.6 gram
Compliances		Not Applicable RoHS Compliant
Certifications		UL Recognized
Product Tradename		None
Product Type		High speed square body fuse
Product Sub Type		None
Electrical data		
Amperage Rating		315 A
Voltage rating		690 V
Interrupt rating		50 kAIC
Class		Class aR
Product specifications		
Application		IGBT circuits, semiconductor protection
Fuse type		Bolted tag
Fuse indicator		None
Fuse size		000

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		000
Type of current		DC
Rated voltage AC	V	
Rated voltage DC	V	690
Rated current	A	315
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	50
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	60
Mounting holes		M8
Centre-to-centre distance of connections	mm	73.8