DATASHEET - FUSE 200A 1000V DC 000FU/90 AR UR



Fuse-link, high speed, 200 A, DC 1000 V, 50 kA, size 000, 24 x 36 x 115 mm, aR, IEC



Part no. FUSE 200A 1000V DC 000FU/90 AR UR Catalog No. 170M1811

Similar to illustration

| Delivery program | | | |
|----------------------|---|----|-------------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | Α | 200 |
| Rated voltage | | | DC 1000 V |
| Construction size | | | size 000 |
| Size | | | 24 x 36 x 115 mm |
| Utilization category | | | aR |
| Breaking Capacity | | kA | 50 |
| Standard/Approval | | | IEC |
| Shape | | | square body with offset bolted tags |

Technical data ETIM 8.0

| icciniical uata Ettivi o.v | | |
|---|----------------------|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) | | |
| Electric engineering, automation, process control engineering / Electrical installation, de | vice / Safety fuse i | nserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |
| Fuse construction type according to IEC 60269 | | Other |
| Type of current | | |
| Rated voltage AC | V | |
| Rated voltage DC | V | 1000 |
| Rated current | Α | 200 |
| Utilization category | | aR (accompanied semiconductor protection) |
| Breaking capacity | kA | |
| Colour code | | |
| Type of fuse status indicator | | None |
| Power loss at rated current | W | 43 |
| Mounting holes | | |
| Centre-to-centre distance of connections | mm | |