



Fuse-link, high speed, 160 A, DC 750 V, 80 kA, compact size 1, 41 x 59 x 128 mm, aR, IEC, type K indicator



Part no. **FUSE 160A 750VDC 1C/A124 PC GR**
 Catalog No. **170M2005**

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	160
Rated voltage			DC 750 V
Construction size			compact size 1
Size			41 x 59 x 128 mm
Utilization category			aR
Status indicator			type K indicator
Breaking Capacity		kA	80
usable for size/applications			traction third rail
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			Other
Type of current			
Rated voltage AC		V	
Rated voltage DC		V	
Rated current		A	160
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	
Colour code			
Type of fuse status indicator			Other
Power loss at rated current		W	
Mounting holes			
Centre-to-centre distance of connections		mm	

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/2ef86aed-e370-419c-ad0a-89df8d9dab6c.pdf
-------------------------	---