

# DATASHEET - FUSE 450A 750VDC A3/A130 PC GR



Fuse-link, high speed, 450 A, DC 750 V, 110 kA, size 3, 75 x 88 x 131 mm, gR, IEC, type K indicator



Referencia **FUSE 450A 750VDC A3/A130 PC GR**  
Catalog No. **170M2010**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	450
Rated voltage			DC 750 V
Construction size			size 3
Size			75 x 88 x 131 mm
Utilization category			gR
Status indicator			type K indicator
Breaking Capacity		kA	110
usable for size/applications			traction third rail
Standard/Approval			IEC
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

## Technical data ETIM 7.0

Tipo de corriente			EV000461
Tensión nominal CA			
Corriente nominal			450
Categoría de uso			EV005308
Capacidad de desconexión			110
Código de color			EV000494
Tipo de indicador de estado de fusible			EV000154

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/2ef86aed-e370-419c-ad0a-89df8d9dab6c.pdf">http://www1.cooperbusmann.com/pdf/2ef86aed-e370-419c-ad0a-89df8d9dab6c.pdf</a>
-------------------------	---