

# Eaton 170M2616

Catalog Number: 170M2616

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 160A, 200kAIC, Top fuse status indicator, Fuse, Blade end X blade end, Class aR, DIN 43 620



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed square body fuse	170M2616
	UPC
	051712254144
<b>EAN</b>	<b>Product Length/Depth</b>
5027590442244	233 mm
<b>Product Height</b>	<b>Product Width</b>
66 mm	140 mm
<b>Product Weight</b>	<b>Warranty</b>
218 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

## defaultTaxonomyAttributeLabel

### Type

Fuse

### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

### Amperage Rating

160 A

### Breaking capacity

200 kA

### Fuse indicator

Top fuse status indicator

### Insulated metal gripping lugs (IMGL)

No

### Utilization category

aR (accompanied semiconductor protection)

### Voltage type

AC

### Fuse size

00

### Rated voltage AC

690 V

### Center-to-center distance of connections

78 mm

### Current type

AC

### Mounting dimension

M10

### Class

Class aR

### Clearing (I2T)

13000 at 660 V

### Watt losses

30 W

### Fuse shape

Square body, slotted offset bolted tags

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

### Compliance information

CE 170M Size 00, rated 690 Vac, up to 400A

UKCA 170M Size 00, rated 690 Vac, up to 400A

Pre arc (I2T)

1900

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

00

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)