

Eaton 170M2619

Catalog Number: 170M2619

Eaton Bussmann series high speed square body fuse, 700V (UL), 690 V (IEC), 315A, 200 kAIC, Top fuse status indicator, Fuse, Blade end X blade end, Class aR, DIN 43 620



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M2619
	Packing Unit
	Case Pack
	Pack
	Quantity
	36
	6
Gross Weight	Length
8.34 kg	385 mm
1.39 kg	233 mm
Width	Height
280 mm	175 mm
140 mm	66 mm
Volume	ERP Name
18865 cm ³	SAP-UNITY
12917.52 cm ³	SAP-UNITY
Product Length/Depth	Product Height
233 mm	66 mm
Product Width	Product Weight
140 mm	232 g
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

315 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

68500 at 660 V

Watt losses

55 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Compliance information

CE 170M Size 00, rated 690 Vac, up to 400A

UKCA 170M Size 00, rated 690 Vac, up to 400A

Pre arc (I2T)

10000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

00

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia