

Eaton 170M2620

Catalog Number: 170M2620

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 350A, 200kAIC, Top fuse status indicator, Fuse, Blade end X blade end, Class aR, DIN 43 620



General specifications

Product Name

Eaton Bussmann series high speed square body fuse

Catalog Number

170M2620

Model Code

FUSE 350A 690V 00/80 AR UR

UPC

051712254175

EAN

5027590442299

Product Length/Depth

233 mm

Product Height

66 mm

Product Width

140 mm

Product Weight

233 g

Warranty

Not Applicable

Compliances

CE Marked
RoHS Compliant

Certifications

UL Recognized
IEC Rated



Powering Business Worldwide

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

350 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

91500 at 660 V

Watt losses

60 W

Fuse shape

Square body, slotted offset bolted tags

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Compliance information

CE 170M Size 00, rated 690 Vac, up to 400A

UKCA 170M Size 00, rated 690 Vac, up to 400A

Pre arc (I2T)

13500

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

00

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

/80 Visual indicator

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia