# Eaton 170M2666

# Catalog Number: 170M2666

Fuse-link, high speed, 160 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs



UPC

100 mm

30 mm

Warranty

Product Width

Not Applicable

Certifications UL Recognized IEC Rated

051712254243

Product Length/Depth

Product Name Eaton Bussmann series high speed square body fuse Catalog Number 170M2666

Model Code FUSE 160A 690V 00TN/80 AR UR

EAN 5027590442435

Product Height 67 mm

Product Weight 222.5 g

Compliances CE Marked RoHS Compliant





# defaultTaxonomyAttributeLabel

#### Туре

Fuse

#### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

#### Amperage Rating

160 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

#### Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

78 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

13000 at 660 V

Watt losses

30 W

Fuse shape

Square body, slotted offset bolted tags

## Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Compliance information UKCA 170M Size 00, rated 690 Vac, up to 400A

CE 170M Size 00, rated 690 Vac, up to 400A

### Pre arc (I2T)

1900

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

00

Packaging type Standard

Voltage rating 690 V (IEC), 700 V (UL)

Fuse type DIN 43653 TN/80 Type T Indicator for Micro

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights property of their respective Reserved.

Eaton is a registered trademark.

All other trademarks are

owners.



Eaton.com/socialmedia