

# Eaton 170M2671

Catalog Number: 170M2671

Fuse-link, high speed, 400 A, AC 690 V, DIN 00, aR, DIN, IEC, single indicator, live gripping lugs

## General specifications



<b>Product Name</b>	<b>Catalog Number</b>
Eaton Bussmann series high speed square body fuse	170M2671
	<b>UPC</b>
	051712792141
<b>EAN</b>	<b>Product Length/Depth</b>
5027590442497	100 mm
<b>Product Height</b>	<b>Product Width</b>
67 mm	30 mm
<b>Product Weight</b>	<b>Warranty</b>
236.3333333 g	Not Applicable
<b>Compliances</b>	<b>Certifications</b>
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

## Product specifications

### Interrupt rating

200 kAIC

### Center-to-center distance of connections

78 mm

### Insulated metal gripping lugs (IMGL)

No

### Current type

AC

### Amperage Rating

400 A

### Fuse type

DIN 43653

TN/80 Type T Indicator for Micro

### Fuse system (according to IEC 60269)

Other

### Fuse size

00

### Voltage rating

690 V (IEC), 700 V (UL)

### Fuse indicator

Top fuse status indicator

### Construction size

00

### Clearing (I2T)

125000 at 660 V

### Rated voltage AC

690 V

### Color

None

### Connection

Blade end x blade end

### Mounting dimension

M10

### Utilization category

aR (accompanied semiconductor protection)

## Resources

### Catalogs

Bussmann series complete full line catalog no. 1007

### Compliance information

UKCA 170M Size 00, rated 690 Vac, up to 400A

CE 170M Size 00, rated 690 Vac, up to 400A

#### Watt losses

70 W

#### Type

Fuse

#### Fuse shape

Square body, slotted offset bolted tags

#### Breaking capacity

200 kA

#### Class

Class aR

#### Pre arc (I2T)

18000

#### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

#### Voltage type

AC

#### Packaging type

Standard



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)