

Eaton 170M2721

Catalog Number: 170M2721

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 400A, 200 kAIC, Top fuse status indicator, Fuse, Class aR, DIN 43 620



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M2721
	UPC
	051712794817
EAN	Product Length/Depth
5027590442978	75 mm
Product Height	Product Width
77 mm	163 mm
Product Weight	Warranty
211 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

400 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

64 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I²T)

125000 at 660 V

Watt losses

70 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

170M2721-Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

18000

Color

None

Interrupt rating

200 kAIC

Construction size

00

Mounting method

DIN 43 620

Flush

Packaging type

Standard

Voltage rating

690 V (IEC)

Fuse type

Flush end

00B/60 Visual indicator

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)