Eaton 170M2763

Catalog Number: 170M2763

Eaton Bussmann series high speed square body fuse, fuse-link, high speed, 80 A, AC 690 V, size 00, 30 x 62 x 64 mm, gR, IEC, single indicator





Eaton Bussmann series high speed square body fuse

UPC

051712254441

Product Length/Depth

75 mm

Product Width

163 mm

Warranty

Not Applicable

Certifications

UL Recognized

IEC Rated

Catalog Number

170M2763

Model Code

FUSE 80A 690V 00BTN/60 GR

EAN

5027590443432

Product Height

77 mm

Product Weight

216.6 g

Compliances

CE Marked

RoHS Compliant



default Taxonomy Attribute Label

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers **Amperage Rating** 80 A Breaking capacity 200 kA Fuse indicator Top fuse status indicator Insulated metal gripping lugs (IMGL) No Utilization category gR (general purpose semiconductor protection) Voltage type AC Fuse size 00 Rated voltage AC 690 V Center-to-center distance of connections 64 mm Current type AC Mounting dimension M8 Class Class gR Clearing (I2T) 2100 at 660 V Watt losses 15 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

170M2763~Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Pre arc (I2T)

310

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type T Indicator for micro

Connection

Blade end x blade end

Construction size

00

Mounting method

DIN 43 620

Flush

Packaging type

Standard

Voltage rating

690 V (IEC)

Fuse type

Flush end

00BTN/60 Type T indicator for micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia