

Eaton 170M2765

Catalog Number: 170M2765

Fuse-link, high speed, 125 A, AC 690 V, size 00, 30 x 62 x 64 mm, aR, IEC, single indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M2765
	UPC
	051712254465
EAN	Product Length/Depth
5027590443456	75 mm
Product Height	Product Width
77 mm	163 mm
Product Weight	Warranty
215.4 g	Not Applicable
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

125 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

00

Rated voltage AC

690 V

Center-to-center distance of connections

64 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I²T)

6950 at 660 V

Watt losses

25 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

170M2765-Eaton Bussmann series high speed square body fuse

Pre arc (I2T)

1000

Color

None

Interrupt rating

200 kAIC

Fitted with:

Type T Indicator for micro

Connection

Blade end x blade end

Construction size

00

Mounting method

DIN 43 620

Flush

Packaging type

Standard

Voltage rating

690 V (IEC)

Fuse type

Flush end

00BTN/60 Type T indicator for micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia