

Eaton 170M3108

Catalog Number: 170M3108

Fuse-link, high speed, 40 A, AC 690 V, compact DIN 1, 45 x 59 x 104 mm, aR, DIN, IEC, single indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3108
	Model Code
	FUSE 40A 690V 1*KN/80 AR UC
EAN	UPC
5027590443869	051712254793
Product Length/Depth	Product Height
305 mm	65 mm
Product Width	Product Weight
145 mm	310 g
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

40 A

Breaking capacity

200 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1*

Rated voltage AC

690 V

Center-to-center distance of connections

76.4 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

270 at 660 V

Watt losses

9 W

Clearing loss

9

Resources

Compliance information

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Technical data sheets

720014 DIN 43653 690V

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

40

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

Other

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

KN/80 Type K Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)