

Eaton 170M3219

Catalog Number: 170M3219

Fuse-link, high speed, 400 A, AC 690 V, compact DIN 1, 45 x 58 x 134 mm, aR, DIN, IEC, type T indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3219
	Model Code
	FUSE 400A 690V 1*TN/110 AR UC
EAN	UPC
5027590445610	051712255264
Product Length/Depth	Product Height
305 mm	65 mm
Product Width	Product Weight
145 mm	339.5 g
Compliances	Certifications
CE Marked	UL Recognized
RoHS Compliant	IEC Rated

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

400 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1*

Rated voltage AC

690 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I2T)

105000 at 660 V

Watt losses

60 W

Clearing loss

60

Resources

Compliance information

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Technical data sheets

720014 DIN 43653 690V

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

15000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

Other

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/110 Type T Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)