

Eaton 170M3415

Catalog Number: 170M3415

Eaton Bussmann series high speed square body fuse, 700V (UL), 690V (IEC), 200A, 200 kAIC, Top fuse status indicator, Fuse, Class aR, Flush

General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M3415
	UPC
	051712799546
EAN	Product Length/Depth
5027590447614	155 mm
Product Height	Product Width
45 mm	90 mm
Product Weight	Warranty
245.8333333 g	Not Applicable
Compliances	Certifications
CE Marked	IEC Rated
RoHS Compliant	UL Recognized



defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

200 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1*

Rated voltage AC

690 V

Center-to-center distance of connections

50 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I2T)

15000 at 660 V

Watt losses

35 W

Fuse shape

Square body, flush end contacts

Resources

Catalogs

170M3415–Eaton Bussmann series high speed square body fuse

Bussmann series complete full line catalog no. 1007

Compliance information

CE Fuse-links for the protection of semiconductor devices, sz1* up to 630A

UKCA Fuse-links for the protection of semiconductor devices, sz1* up to 630A

Pre arc (I2T)

2200

Color

None

Interrupt rating

200 kAIC

Construction size

Other

Mounting method

Flush

Packaging type

Standard

Voltage rating

690 V

Fuse type

Flush end

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)