



Fuse-link, high speed, 800 A, AC 690 V, size 1, 51 x 69 x 138 mm, aR, DIN, IEC, type K indicator

Part no. **FUSE 800A 690V 1KW/110 AR**  
 Catalog No. **170M4134**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	800
Rated voltage			AC 690 V
Construction size			size 1
Size			51 x 69 x 138 mm
Utilization category			aR
Status indicator			type K indicator
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)

## Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])			
Fuse construction type according to IEC 60269			1
Type of current			AC
Rated voltage AC		V	690
Rated voltage DC		V	
Rated current		A	800
Utilization category			aR (accompanied semiconductor protection)
Breaking capacity		kA	200
Colour code			None
Type of fuse status indicator			Top fuse status indicator
Power loss at rated current		W	
Mounting holes			M10
Centre-to-centre distance of connections		mm	108