

Eaton 170M4217

Catalog Number: 170M4217

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 66 x 138 mm, aR, DIN, IEC, type T indicator



General specifications

Product Name	Catalog Number
Eaton Bussmann series high speed square body fuse	170M4217
	EAN
	5027590451918
UPC	Product Length/Depth
051712258159	245 mm
Product Height	Product Width
62 mm	142 mm
Product Weight	Compliances
499 g	CE Marked
	RoHS Compliant
Certifications	
UL Recognized	
IEC Rated	

defaultTaxonomyAttributeLabel

Type

Fuse

Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

Amperage Rating

700 A

Breaking capacity

200 kA

Fuse indicator

Top fuse status indicator

Insulated metal gripping lugs (IMGL)

No

Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC

Fuse size

1

Rated voltage AC

690 V

Center-to-center distance of connections

108 mm

Current type

AC

Mounting dimension

M10

Class

Class aR

Clearing (I₂T)

725000 at 660 V

Watt losses

85 W

Clearing loss

85

Resources

Compliance information

CE Fuse-links for the protection of semiconductor devices, Size 1 up to 900A

UKCA Fuse-links for the protection of semiconductor devices, Size 1 up to 900A

Technical data sheets

720014 DIN 43653 690V

Fuse shape

Square body, slotted center bolted tags

Pre arc (I2T)

34000

Color

None

Interrupt rating

200 kAIC

Connection

Blade end x blade end

Construction size

1

Packaging type

Standard

Voltage rating

690 V (IEC), 700 V (UL)

Fuse type

DIN 43653

TN/110 Type T Indicator for Micro

Bolted tag

Fuse system (according to IEC 60269)

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)