

Fuse-link, high speed, 500 A, AC 690 V, size 1, 53 x 69 x 111 mm, aR, IEC, single indicator



170M4364

Similar to illustration

General specifications	
Product name	Eaton Bussmann series high speed square body fuse
Part no.	170M4364
EAN	5027590452366
Product Length/Depth	210 millimetre
Product height	80 millimetre
Product width	160 millimetre
Product weight	500 gram
Compliances	CE Marked RoHS Compliant
Certifications	UL Recognized IEC Rated
Product Tradename	None
Product Type	High speed square body fuse
Product Sub Type	None
Electrical data	
Amperage Rating	500 A
Voltage rating	690 V
Interrupt rating	200 kAIC
Class	Class aR
Clearing (I2T)	170000 at 660 V
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type	French style EKN/Type K Indicator for Micro Bolted tag
Fuse indicator	Centre fuse status indicator
Fuse size	1

Technical data ETIM 9.0

Toomitod data 21111 olo		
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, de	vice / Safety fuse	inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])
Fuse system according to IEC 60269		Other
Fuse construction type according to IEC 60269		1
Type of current		AC
Rated voltage AC	V	690
Rated voltage DC	V	
Rated current	Α	500
Utilization category		aR (accompanied semiconductor protection)
Breaking capacity	kA	200
Colour code		None
Type of fuse status indicator		Centre fuse status indicator
Power loss at rated current	W	72
Mounting holes		M10
Centre-to-centre distance of connections	mm	86.5