

Fuse-link, high speed, 500 A, AC 690 V, size 1, aR, IEC, UL, single indicator



170M4414

General specifications	
Product name	Eaton Bussmann series high speed square body fuse
Part no.	170M4414
EAN	5027590452649
Product Length/Depth	107 millimetre
Product height	63 millimetre
Product width	53 millimetre
Product weight	382 gram
Compliances	RoHS Compliant CE Marked
Certifications	IEC Rated UL Recognized
Product Tradename	None
Product Type	High speed square body fuse
Product Sub Type	None
Electrical data	
Amperage Rating	500 A
Voltage rating	690 V (IEC), 700 V (UL)
Interrupt rating	200 kAIC
Class	Class aR
Clearing (I2T)	170000 at 660 V
Product specifications	
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type	Flush end B/Visual indicator
Fuse indicator	Top fuse status indicator
Fuse size	1

Technical data ETIM 9.0

Teeliniedi data ETIW 5.0					
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)					
Electric engineering, automation, process control engineering / Electrical in	stallation, device / Sa	fety fuse	inserts / Safety fuse inserts (unspecified) (ecl@ss13-27-14-20-90 [BAB264016])		
Fuse system according to IEC 60269			IEC 60269-4 flush end connections type A		
Fuse construction type according to IEC 60269			1		
Type of current			AC		
Rated voltage AC		V	690		
Rated voltage DC		V			
Rated current		Α	500		
Utilization category			aR (accompanied semiconductor protection)		
Breaking capacity		kA	200		
Colour code			None		
Type of fuse status indicator			Top fuse status indicator		
Power loss at rated current		W	72		
Mounting holes			M8		
Centre-to-centre distance of connections		mm	51		