# Eaton 170M4442

# Catalog Number: 170M4442

Fuse-link, high speed, 350 A, AC 1250 V, size 1, 53 x 69 x 80 mm, aR, IEC, UL, single indicator



Product Name Eaton Bussmann series high speed square body fuse

EAN 5996516013267

Product Height 59 mm

Product Weight 2095 g

Compliances CE Marked RoHS Compliant UPC 051712258838 Product Length/Depth 75 mm

Catalog Number

170M4442

Product Width 45 mm

Warranty Not Applicable

#### Certifications

UL Recognized IEC Rated





## defaultTaxonomyAttributeLabel

#### Туре

Fuse

#### Application

Semiconductor, DC Common bus, DC drives, power converters/rectifiers

#### Amperage Rating

350 A

Breaking capacity

100 kA

Fuse indicator

Centre fuse status indicator

Insulated metal gripping lugs (IMGL)

No

#### Utilization category

aR (accompanied semiconductor protection)

Voltage type

AC/DC

Fuse size

1

Rated voltage AC

1250 V

Center-to-center distance of connections

81.1 mm

Current type

AC

Mounting dimension

M8

Class

Class aR

Clearing (I2T) 125000 at 1000 V, 165000 at 1250 V

Watt losses

70 W

Fuse shape Square body, flush end contacts

### Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Compliance information CE HS Size 1, 1250 V, rated up to 550A UKCA HS Size 1, 1250 V, rated up to 550A

#### Pre arc (I2T)

20000

Color None

Interrupt rating

100 kAIC

Construction size

1

Mounting method

Flush

Packaging type

Standard

Voltage rating 1250 V (IEC), 1300 V (UL)

Fuse type Flush end

BKN/80 Type K Indicator for Micro

Fuse system (according to IEC 60269)

IEC 60269-4 flush end connections type A



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights property of their respective Reserved.

Eaton is a registered trademark.

All other trademarks are

owners.



Eaton.com/socialmedia